



- Notes:
1. Voltage rating: 30V ac
  2. Current rating: 1.5 A max
  3. Contact resistance: 50m $\Omega$  max
  4. Insulation resistance: 20M $\Omega$  min
  5. Dielectric withstanding voltage: 500V AC
  6. Operating Temperature: -20°C to 50°C

- Material:
1. Insert: ABS
  2. Frame: Polyamide UL94V-2
  3. Shell: Nickel plated steel
  4. Contacts: Gold Plated
  5. UL94V-2



TOLERANCE  
 NO DEC. PLACE  $\pm$   
 1 DEC. PLACE  $\pm$   
 2 DEC. PLACE  $\pm$   
 HOLE  $\varnothing$   
 ANGLES  $\pm$   
 UNLESS  
 OTHERWISE STATED

DO NOT SCALE



VARIANTS	
PART NO.	HOLE DETAILS
CP30208N	HOLE $\varnothing 3.50$ X CSK $82^\circ$ X $\varnothing 5.85$
CP30208NX	PLAIN HOLE $\varnothing 2.50$

ISS.	1
AMEND	ISSUED
DATE	12/02/2015

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Cables / IEEE 1394 Cables category](#):*

*Click to view products by [Cliff manufacturer](#):*

Other Similar products are found below :

[68768-0173](#) [FNY-W6003-01](#) [88764-0800](#) [13805532](#) [148700-1](#) [17-200621](#) [17-250051P](#) [954](#) [AC102012-2](#) [IP-USB1\(C10\)S-RW](#)  
[CABLE/RTP/USB/DT](#) [0847290003](#) [10115240-12200LF](#) [RS232-GTD](#) [USBFTVX2SA2N03A](#) [USBFTV2SA2N03A](#) [1689404-1](#) [FTP-](#)  
[629Y401](#) [FTP-628Y402](#) [943301-001](#) [FNY-W6022](#) [FNY-W6003-03](#) [1310-1015-05](#) [1310-1019-04](#) [0887283402](#) [UA-30AMFM-SL7B02](#) [UA-](#)  
[30AMFM-SL7B01](#) [UA-30AFM-LD7B03](#) [UA-30AMFM-SL7B03](#) [USBAPSCC7202A](#) [UES-1001A160](#) [UES-1003A160](#)  
[USBFTVX7SA2N20A](#) [USBFTVX2SA2N20A](#) [USBFTV2PEMSA2N10A](#) [FTP-629Y602](#) [USBCAMCM100](#) [USB A/F\\*2 to 2.54 2\\*5P-SH](#)  
[L=400mm](#) [EP-CBUSB10P2FLT](#) [1310-1033-01](#) [1310-1037-04](#) [ASR-USB](#) [68784-0075](#) [17-241361](#) [17-230471](#) [217B-BC02](#) [USB-29](#) [19800-](#)  
[010500-200-RS](#) [USB+MINI DIN 6P WITH BKT](#) [088738-8100](#)