



Heavy Duty Light Meters

Datalogging Model Available

Automatically stores up to 16,000 readings or manually store/recall up to 99 readings.

Features:

- HD450 Datalogger model automatically stores up to 16,000 readings or manually store/recall up to 99 readings
- Wide range to 40,000Fc or 400,000 Lux
- · Cosine and color corrected measurements
- Utilizes precision silicon photo diode and spectral response filter
- Peak mode (10µS) captures highest reading
- · Relative mode indicates change in light levels
- Min/Max and Data Hold
- Large backlit LCD display with 40-segment bar graph
- Heavy Duty rugged double molded housing
- Built-in USB port
- Includes light sensor with 3ft (1m) cable and protective cover, Windows[®] compatible software with USB cable, hard carrying case, and 9V battery



Specifications	
Fc Range	40, 400, 4000, 40.00kFc
Lux Range	400, 4000, 40k, 400kLux
Accuracy	±5% rdg
Max Resolution	0.01Fc/0.1Lux
Datalogging	16,000 continuous readings; 99 selected readings
PC interface	USB
Dimensions	6.7 x 3.1 x 1.6" (170 x 80 x 40mm)
Weight	13.7oz (390g)

Ordering Information:

HD400Heavy Duty Light Meter HD400-NIST ..Heavy Duty Light Meter with NIST Certificate HD450Heavy Duty Datalogging Light Meter HD450-NIST ..Heavy Duty Datlogging Light Meter with NIST Certificate TR100Tripod for meters with tripod mount feature

www.extech.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below :

 CW40
 F150C10E3DRT
 F150LTC20
 F150CD10E2
 F150L75
 F150LRS
 S-11
 FLUKE-LDG
 382153
 FM100
 RH210
 382253
 MO290-P

 GEO-CABLE-REEL-50M
 T197914
 RD300-L
 IR11BD
 IR11GM
 IR21BD
 IR31CE
 IR32BC
 IR33BC
 MP7217TC
 NGM-1
 SGX

 7NH3
 UT381
 F150-SLC50
 AW-CO-1000
 AW-NmHc-100
 3.000.401
 AX-7535
 CS-9S6SS-A
 P 2800 A
 P 2801
 P 2802
 P 5039
 P 5130
 P

 5055
 P 5060
 P 5065
 P 5086
 P 5090
 P 5115
 P 5135
 P 5140
 P 5145
 P 5150
 P 5160