

CRC Graphite Assembly Paste + MoS₂

Ref. : 10422

1. GENERAL DESCRIPTION

A universal assembly spray paste.

Special sprayable paste which contains a combination of the extremely pressure-resistant solid lubricants molybdenum disulphide (MoS₂) and graphite, stabilised in adhesive mineral oil.

2. FEATURES

- High load-carrying capacity reducing the appearance of the grooves when inserting components
- Water-repellent
- Good corrosion protection
- Oxidation resistant
- High thermal stability (up to 650°C)
- Very good adhesion
- Prevents seizing
- Prevents fretting corrosion, scuffing and stick-slip
- Constant ratio of starting torque to initial tension
- Smooths out rough surfaces

3. APPLICATIONS

- Mounting of longitudinal press fits, eg. for bolts and bearing seats.
- Assembly of seals and screws.
- Surface treatment of rolling and sliding bearings to improve the running-in and to extend lifetime.
- Lubrication of guides and joints with very slow sliding movement.
- Bearing lubricant for wheel bearings and kiln carts.
- Lubrication of all types of open gears.
- Running-in lubricant of new gear wheels.


4. DIRECTIONS

- Shake can very well till agitator ball is free.
- Apply a thin, even layer.
- As running-in for rolling and sliding bearings, polish the applied product with a soft cloth. Remove any excess.
- As running-in for new gear wheels : let the gears operate at a low speed and with a low load (eg. moving by hand) without the operating lubricant. Then fill the system with the lubricant.



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC Graphite Assembly Paste + MoS2

Ref. : 10422

5. TYPICAL PRODUCT DATA (without propellant)

Temperature range	:	-30°C to +650°C
Load carrying capacity (four-ball welding load) (DIN 51350)	:	7.000 N
Flash point of aerosol	:	< 0°C

6. PACKAGING

aerosol : 12 x 400ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10422 03 0799 01
Date : 25 september 2003



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Chemicals](#) category:

Click to view products by [CRC](#) manufacturer:

Other Similar products are found below :

[HANDPAD](#) [1624-10S](#) [3045-QT](#) [3065-15S](#) [3125-9S](#) [5200-WHITE-3OZ](#) [70008073302](#) [1398159-1](#) [S1255-04-34X100FT](#) [3748-Q-58"x8"](#) [FO-25DT](#) [13844](#) [S1009-KIT-A-CS8606](#) [8361-P](#) [2216-GRAY-2OZ](#) [DP100-200ML](#) [1743-2FP](#) [2310-10](#) [VERSIL406](#) [826-450G](#) [SS4120-1P](#) [3789-Q](#) [9729](#) [9223](#) [9176](#) [600-0510](#) [3748PG](#) [04952-00531-00](#) [04952-00533-00](#) [10-50L](#) [3748-Q-5/8"X8"](#) [3764-TC](#) [3M 9087](#) [3M 9088](#) [AS1700](#) [120-320](#) [BLR-15ML](#) [HYBRICX 35C](#) [7552](#) [7558](#) [3748-V-O-Q-5/8"X8"](#) [3764-Q](#) [3779-TC](#) [3797TC](#) [3M 9086](#) [100500F00000G](#) [101800F00000G](#) [1610-5G](#) [1610-G4](#) [1621-5G](#)