

## 0125 KSS Round Type Wiring Duct





- Material: High impact, self-extinguishing, warp-proof 94V-0 PVC.
  Color: Grey. (Brown, Milk, Light grained, Dark Grained available on request).
- Maximum service temperature : 85°C.
- Backed with high quality double sided tape for permanent stick. Good for floor wiring to facilitate trolly pass and to avoid trip.





Unit: mm

	1.	10/	18/4		114	Unit: mn
Item No.		W	W1	Н	H1	Length
RD-20	Grey					
RD-20BN	Brown					
RD-20MW	Milk	20.0	8.0	6.0	4.0	
RD-20LX	Light grained					
RD-20DX	Dark grained					
□ RD-30	Grey					
RD-30BN	Brown					
RD-30MW	Milk	30.0	11.0	8.0	6.0	
RD-30LX	Light grained					
RD-30DX	Dark grained					
□RD-40	Grey					
RD-40BN	Brown					
RD-40MW	Milk	40.0	16.0	9.5	7.0	
RD-40LX	Light grained					
RD-40DX	Dark grained					
□RD-50	Grey					
RD-50BN	Brown					
RD-50MW	Milk	50.0	20.0	11.0	8.0	
RD-50LX	Light grained					
RD-50DX	Dark grained					1M
□RD-60	Grey					
RD-60BN	Brown					
RD-60MW	Milk	60.0	30.0	13.0	9.0	
RD-60LX	Light grained					
□RD-60DX	Dark grained					
□RD-70	Grey					
□RD-70BN	Brown					
RD-70MW	Milk	70.0	40.0	15.0	10.0	
□RD-70LX	Light grained					
□RD-70DX	Dark grained					
□RD-90	Grey					
RD-90BN	Brown					
RD-90MW	Milk	90.0	45.0	19.0	15.0	
RD-90LX	Light grained					
RD-90DX	Dark grained					
□RD-120	Grey					
RD-120BN	Brown					
RD-120MW	Milk	120.0	70.0	25.0	21.0	
RD-120LX	Light grained					
□RD-120DX	Dark grained					

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Non-Heat Shrink Tubing and Sleeves category:

Click to view products by KSS manufacturer:

Other Similar products are found below:

601203-000 CTA-0053 8429-9 8445-7.5 8450 120-116-1-1-09BE 120-116-1-1-09BF 120-116-1-1-09BP 120-116-1-1-12BE 120-116-1-1-12BE 120-116-1-1-12BP 120-123-06 120-123-10 120-125-12BL 120-125-12R 120-125-20R 120-126-09 120-126-09BL 120-126-12 120-126-12BL 12