

Coaxial cable 50 Ω MIL. standards



Applications:
Coaxial braided shielded cable for radio frequency MIL. C 17 F Standards.

Characteristics:
 Conductor: stranded in red copper
 Insulation: Compact PE
 Shield: Braided covering 98%
 O.F.C. red copper
 Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
RG 213 U	1	1 x 50 Ω (3,09 mm ²)	7x0,75	7,3		10,4	100	B	17,5

Conductor Resistance	Capacity Core/shield	Velocity of propagation			
Ω/Km ± 5%	pF/mt	%			
6	100	66			
Impedance	Voltage	Operative Temperature			
Ω ± 3%	V	°C			
50	5000	-15 / +70			
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
4,5	6,7	9,9	14,3	21,3	24,3

Coaxial video cable 75 Ω Ø mm. 5,0



Applications:
Professional high efficiency coaxial cable with double shield for digital video SAT installation as for example for Decoder or SAT receivers, etc. The main feature of this cable is the small external diameter and good attenuation values.

Characteristics:
 Conductor: stiff wire in O.F.C. red copper
 Insulation: Gas injected FOAM PEE
 I° Shield: Al./Pet/Al. tape covering 100%
 Braided covering 40%
 O.F.C. tinned copper
 II° Shield: transparent Polyester (Pet)
 Sheath: PVC
 Sheath colours: **Black, White, Red, Green, Blue**
 CT 905/10 - CT 905/25
 Sheath colour: **White**
 Standards: CEI 46-1 C90 131-132
 CEI 12-15 EN 50117



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C905	1	1 x 75 Ω (0,50 mm ²)	1x0,80	3,5		5,0	100	B	2,7
CT905/10 CT905/25		1 x 75 Ω (0,50 mm ²)	1x0,80	3,5		5,0	10x10 mt	M	
					10x25 mt		M		

Conductor Resistance	Capacity Core/shield	Velocity of propagation			
Ω/Km ± 5%	pF/mt ± 2%	%			
40	53	84			
40	53	84			
Impedance	Operative Temperature				
Ω ± 3%	°C				
75	-15 / +70				
Structure Return Loss (SRL) db					
30÷470 MHz	470÷862 MHz	862÷2400 MHz			
> 28	> 26	> 20			
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	470 MHz	800 MHz	860 MHz
5,9	7,8	11,3	17,6	23,0	24,2
1000 MHz	1350 MHz	1750 MHz	2150 MHz	2400 MHz	2700 MHz
26,3	30,8	35,6	40,0	42,2	45,2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coaxial Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[89880-003-1000](#) [633948-877-1000](#) [CY2389-000](#) [8213-010-1000](#) [8221-010-U1000](#) [8233-010-1000](#) [88281-010-500](#) [1322R-010-1000](#) [177799-000](#) [1807A-B59-U1000](#) [9167-010-1000](#) [9251-010-1000](#) [9275-010-U1000](#) [935240-000](#) [9659-010-1000](#) [980704-001](#) [CF2823-000](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#) [144517-000](#) [8-1616396-1](#) [8263-010-U1000](#) [8263 010U500](#) [8268-010-500](#) [8262 010U1000](#) [7915A 009U1000](#) [5024A1311-0](#) [TRC-75-1](#) [1281S5 010250](#) [1281S5 000250](#) [1530A 010U1000](#) [1505A 0081000](#) [9248 010U1000](#) [CO-142BNCX200-001](#) [7809WB 010500](#) [9244 0101000](#) [1694A 0081000](#) [9204 0101000](#) [8241F J5C1000](#) [1530A 0101000](#) [1674A TIN50](#) [7915A 0091000](#) [7915A 010500](#) [TWCH-78-2](#) [TWC-78-1](#)