


# 3M™ Round Conductor Flat Cable

1.0 mm 28 AWG Stranded, PVC

3625 Series



- 28 AWG stranded conductors on 1mm wire spacing is designed for mass termination to metric connectors
- Stranded wire provides flexibility and extended product life
- Zippable for branching or discrete termination
- RoHS compliant

Date Modified: March 23, 2004

TS-0452-10  
Sheet 1 of 2

---

## Physical

### Insulation

Material: Polyvinyl Chloride (PVC)

Color: Gray

### Marking

Standard: None

Canadian Option:  AWM 2651 105C 300V VW1 3M NU  AWM IA 105C 300V FT1  
EU <50V

**Conductors:** 28 AWG 7 × 36 [ 7 × 0.127 ] Tinned Stranded Copper

---

## Electrical

**Voltage Rating:** USA: 300V      Canada: 300V      EU: <50V

**Insulation Resistance:** >1 x 10<sup>10</sup> Ω /10ft [3m]

	<b>Unbalanced</b>	<b>Balanced</b>
<b>Characteristic Impedance:</b>	92 Ω	146 Ω
<b>Capacitance:</b>	54.5 pF/m (16.6 pF/ft)	32.2 pF/m (9.8 pF/ft)
<b>Inductance:</b>	0.46 μH/m (0.14 μH/ft)	0.69 μH/m (0.21 μH/ft)
<b>Propagation Delay:</b>	4.86 ns/m (1.48 ns/ft)	4.69 ns/m (1.43 ns/ft)
<b>Velocity of Propagation:</b>	69%	71%

Note: Unbalanced is measured between ground-signal-ground conductors. Balanced is measured between signal conductors within a pair.

---

## Environmental

**Temperature Rating:** -20° C to +105° C

**Flammability Rating:** USA: VW-1

Canada: FT1

\*RoHS = Directive 2002/95/EC,  
Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment

UL File No.: E42769, Style No.: 2651

**3M**  
**Interconnect Solutions**  
<http://www.3M.com/interconnects/>


3M is a trademark of 3M Company.  
For technical, sales or ordering information call  
**800-225-5373**

# 3M™ Round Conductor Flat Cable

## 1.0 mm 28 AWG Stranded, PVC

3625 Series

Number of Conductors	3M Part Number	Dimension A	Dimension B
06	3625/06	6.00 ± 0.20 [ .236 ]	5.00 ± 0.18 [ .197 ]
08	3625/08	8.00 ± 0.20 [ .315 ]	7.00 ± 0.18 [ .276 ]
10	3625/10	10.00 ± 0.20 [ .394 ]	9.00 ± 0.18 [ .354 ]
12	3625/12	12.00 ± 0.20 [ .472 ]	11.00 ± 0.18 [ .433 ]
14	3625/14	14.00 ± 0.20 [ .551 ]	13.00 ± 0.18 [ .512 ]
16	3625/16	16.00 ± 0.22 [ .630 ]	15.00 ± 0.20 [ .591 ]
18	3625/18	18.00 ± 0.22 [ .709 ]	17.00 ± 0.20 [ .669 ]
20	3625/20	20.00 ± 0.22 [ .787 ]	19.00 ± 0.20 [ .748 ]
22	3625/22	22.00 ± 0.22 [ .866 ]	21.00 ± 0.20 [ .827 ]
24	3625/24	24.00 ± 0.22 [ .945 ]	23.00 ± 0.20 [ .906 ]
26	3625/26	26.00 ± 0.22 [ 1.024 ]	25.00 ± 0.20 [ .984 ]
28	3625/28	28.00 ± 0.22 [ 1.102 ]	27.00 ± 0.20 [ 1.063 ]
30	3625/30	30.00 ± 0.25 [ 1.181 ]	29.00 ± 0.23 [ 1.142 ]
32	3625/32	32.00 ± 0.25 [ 1.260 ]	31.00 ± 0.23 [ 1.220 ]
34	3625/34	34.00 ± 0.25 [ 1.339 ]	33.00 ± 0.23 [ 1.299 ]
36	3625/36	36.00 ± 0.25 [ 1.417 ]	35.00 ± 0.23 [ 1.378 ]
38	3625/38	38.00 ± 0.25 [ 1.496 ]	37.00 ± 0.23 [ 1.457 ]
40	3625/40	40.00 ± 0.25 [ 1.575 ]	39.00 ± 0.23 [ 1.535 ]
42	3625/42	42.00 ± 0.25 [ 1.654 ]	41.00 ± 0.23 [ 1.614 ]
44	3625/44	44.00 ± 0.25 [ 1.732 ]	43.00 ± 0.23 [ 1.693 ]
46	3625/46	46.00 ± 0.25 [ 1.811 ]	45.00 ± 0.23 [ 1.772 ]
48	3625/48	48.00 ± 0.25 [ 1.890 ]	47.00 ± 0.23 [ 1.850 ]
50	3625/50	50.00 ± 0.25 [ 1.969 ]	49.00 ± 0.23 [ 1.929 ]




mm [Inch]		
Tolerance Unless Noted		
	.0	.00 .000
mm	± .3	± .13

Note: Red marking on one edge of the cable designates wire #1.

[ ] Dimensions for Reference only

### Ordering Information



Note: Available in 30 m and 100 m roll length. Please specify when ordering.

TS-0452-10  
Sheet 2 of 2

### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.



### **Electronic Solutions Division**

6801 River Place Blvd.  
Austin, TX 78726-9000  
[www.3M.com/esd](http://www.3M.com/esd)

### **Warranty; Limited Remedy; Limited Liability.**

This product will be free from defects in material and manufacture for a period of 1 year from the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Ribbon Cables / IDC Cables](#) category:*

*Click to view products by [3M](#) manufacturer:*

Other Similar products are found below :

[FSK-12A Ribbon Cable, 6 Pin, 500mm](#) [AWG28-10G EHV3C EHV4C EHV5C](#) [cab-LVDV-PWR-10-15 FSP-25A Ribbon Cable, 4 Pin, 350mm](#)  
[Ribbon Cable, 6 Pin, 300mm](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [92315-1408](#) [100063-0094](#) [100063-0106](#) [100063-0102](#)  
[100063-0104](#) [MMSD-02-20C-F-15.00-S-K](#) [100063-0099](#) [100063-0105](#) [100063-0095](#) [100063-0103](#) [100063-0093](#) [100063-0091](#) [2200000068](#)  
[100063-0092](#) [100063-0101](#) [100063-0100](#) [100063-0097](#) [TFSDT-08-28-H-15.00-S](#) [S1SD-02-30-GF-09.00-L](#) [MMSD-02-22C-F-15.00-S-K](#)  
[S1SS-02-28C-GF-02.00-L](#) [S1SDT-02-28-GF-03.00-L](#) [2-1589735-3](#) [JSM015PP2DCC23N](#) [92301-0283](#) [TCSD-22-D-26.00-01](#) [S1SST-07-30-](#)  
[GF-06.00-L](#) [T2SD-20-24-L-07.87-TR-NUS](#) [DS1057-01-44A282R-30.5](#) [FFSD-06-S-17.00-01-N](#) [IDSS-03-D-20.00-T](#) [TCMD-17-S-36.00-01-](#)  
[SR](#) [92301-0718](#) [839023](#) [490107670612S](#) [MMSDT-06-20-S-05.5-D-K-LDX](#) [IDD-04-G](#)