

Cirrus 25



Cirrus 25		25/1			25/2			
Nominal Power	at 10°C	5W	10W	20W	10W	20W	30W	40W
Typical Max. In-Rush Current (A) RMS	at 12V AC	0.5	1.5	3	-	2.5	4	5
Typical Max. In-Rush Current (A) RMS	at 24V AC	1.3	1.3	3	2.5	-	5.5	9.5
Typical Max. In-Rush Current (A) RMS	at 115/230V AC	-	-	-	-	0.5 / 2.5	1 / 3.5	1 / 3.5
Electrical Protection Class		III / SELV	III / SELV	III / SELV	III / SELV	I	I	I
Ingress Protection		IP20	IP20	IP20	IP20	IP20	IP20	IP20
Fan Volumetric Flow	(m ³ /hr)	5.1	5.1	5.1	5.1	5.1	5.1	5.1
Fan Life Time - L10	at 40°C (hrs)	120.000	120.000	120.000	120.000	120.000	120.000	120.000
Fan Operating Temperature Range	(°C)	-10 to +70	-10 to +70	-10 to +70	-10 to +70	-10 to +70	-10 to +70	-10 to +70
Nominal Input Voltage Fan	(V)	12 DC, 12 AC or 24 AC/DC			24 AC/DC	12 DC, 12 AC or 24 AC/DC		
Nominal Input Voltage Heater	(V)	12 DC, 12 AC or 24 AC/DC			24 AC/DC	12 AC/DC or 115/230	12 AC/DC or 24 AC/DC or 115/230	
Dimensions	Cross Section (mm)	26 x 27	26 x 27	26 x 27	26 x 27	26 x 27	26 x 27	26 x 27
Length	(mm)	50	50	50	72	72	72	72
Weight	(g)	60	60	60	90	90	90	90
Finger Guards at Outlet	(High Voltage Supply)	N / A	N / A	N / A	N / A	Yes	Yes	Yes
Finger Guards at Outlet	(Low Voltage Supply)	Optional	Optional	Optional	Optional	Optional	Optional	Optional


Type	Size	Power	Fan input	AC / DC	Heater Voltage	Finger guard outlet	DIN clip
	1 / 2		12 / 24			1 / 0	1 / 0
C25	2	30W	12V	DC	24V	0	1

Order Code Example: C25 / 2 - 30W - 12V - DC - 24V - 0 - 1


When specifying 12V fan, select either ac or dc operation. For 24V fan operation ac or dc can be applied.
* Other power outputs available on request.



Model 25/1



Model 25/2



Features:

- High power to size ratio
- Lightweight
- Easy to fit
- pre-wired
- Independent fan circuit to aid climate cooling

Options:

- Finger guard at outlet
- Smartcon® - Cable to allow AC fan supply and/or 24V fan supply
- Fixings - 35mm DIN Rail clip (EN50022)

DBK David+Baader GmbH

Industrial Heating

Nordring 26
76761 Rülzheim

Phone: +49 (0) 7272 7704 - 0
Fax: +49 (0) 7272 7704 - 1249

info@dbk-group.de
www.dbk-group.de

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Thermal Interface Products](#) category:

Click to view products by [DBK Technitherm](#) manufacturer:

Other Similar products are found below :

[63072-2-4013](#) [64442-1-7612](#) [FGN80-2](#) [PFM-172-60](#) [95778-1-5171](#) [A-40](#) [ACDIN4001-01-S](#) [APA502-80-001](#) [188761F00000G](#) [95779-1-5171](#) [9601-7](#) [9614-2-4013](#) [189790F00000](#) [189951F00000G](#) [2103-4-7320](#) [CN9565-000](#) [31570-2-4013](#) [LZ24-1](#) [4103G](#) [450-20-0025](#) [5300AC](#) [1.500G](#) [53-77-13ACG](#) [450-20-0017](#) [4949G](#) [08121](#) [08133](#) [08151](#) [08188](#) [08196](#) [10637-4-1040](#) [54476-2-4013](#) [71883-2-4053](#) [188651F00000G](#) [64445-1-7612](#) [66786-4-7320](#) [TP0001](#) [4952G](#) [4860](#) [450-20-0148](#) [88601-2-2929](#) [SC80-W2](#) [09450-M45](#) [09362-M45](#) [V6516C](#) [A17713-05](#) [A17690-06](#) [A17690-10](#) [A17690-05](#) [A17690-03](#) [A17775-05](#)