Insulation

## Heat Shrinkable Tubing 3:1 in a Kit

## ShrinKit 321-A - with adhesive liner

The black tubing is mainly used for environmental sealing of splices and connectors. The transparent tubing is typically used for protection of cable markers.

## **Features and Benefits**

- · Adhesive lined heat shrink tubing
- Attractive and reusable kit ideal for assembling and identification
- Inner wall melts when heated and is forced into gaps
- Adhesive forms seal against moisture as tubing cools
- Black tubing mainly for the protection of connectors and splices
- Clear tubing ideal for protection of printed label markers
- Case can be re-used for storing nails, screws, nuts, fish hooks, etc.
- Compartment size changeable by simply moving yellow space dividers




ShrinKit 321-A.

| MATERIAL                            | Polyolefin, cross-linked (PO-X)                   |  |  |  |
|-------------------------------------|---|--|--|--|
| Shrink Ratio                        | 3:1   |  |  |  |
| <b>Operating Temperature</b>        | -55 °C to +110 °C                                 |  |  |  |
| Minimum Shrink<br>Temperature       | +110 °C   |  |  |  |
| Longitudinal change after shrinkage | +1 %/-15 % max.                                   |  |  |  |
| Dielectric Strength                 | 15 kV/mm according to IEC 60684 P2                |  |  |  |
| Flammability                        | self-extinguishing (except for transparent)       |  |  |  |
| Insulation Class                    | A (VDE 0530)                                      |  |  |  |
| Specifications                      | SAE - AMS - DTL-23053/4 Class 3<br>(except clear) |  |  |  |



One Step to the Web!





Heat Shrinkable Tubing 3:1 with adhesive



| сомр. | Supplied<br>Ø D min. | Recov.<br>Ø d max. | Length<br>(L) | Wall<br>(WT) | Colour           | Content<br>(pcs.) | Article-No. |
|-------|----------------------|--------------------|---------------|--------------|------------------|-------------------|-------------|
| 1     | 24.0                 | 8.0                | 200.0         | 2.50         | Black (BK)       | 5                 |             |
| 2     | 12.0                 | 4.0                | 65.0          | 1.70         | Transparent (CL) | 15                |             |
| 2     | 6.0                  | 2.0                | 50.0          | 1.10         | Black (BK)       | 20                |             |
| 3     | 6.0                  | 2.0                | 50.0          | 1.10         | Transparent (CL) | 20                |             |
| 4     | 12.0                 | 4.0                | 65.0          | 1.70         | Black (BK)       | 15                |             |
| -     | 3.0                  | 1.0                | 50.0          | 1.00         | Black (BK)       | 50                | 50          |
| 5     | 3.0                  | 1.0                | 50.0          | 1.00         | Transparent (CL) | 50                |             |
| c     | 6.0                  | 2.0                | 35.0          | 1.10         | Black (BK)       | 30                | 380-03003   |
| 6     | 6.0                  | 2.0                | 35.0          | 1.10         | Transparent (CL) | 30                |             |
| 7     | 24.0                 | 8.0                | 200.0         | 2.50         | Transparent (CL) | 5                 |             |
| 8     | 12.0                 | 4.0                | 100.0         | 1.70         | Black (BK)       | 15                |             |
| 9     | 12.0                 | 4.0                | 100.0         | 1.70         | Black (BK)       | 15                |             |
| 10    | 12.0                 | 4.0                | 100.0         | 1.70         | Transparent (CL) | 15                |             |
| 11    | 3.0                  | 1.0                | 40.0          | 1.00         | Black (BK)       | 50                |             |
| 11    | 3.0                  | 1.0                | 40.0          | 1.00         | Transparent (CL) | 50                |             |

All dimensions in mm. Subject to technical changes.



For product specific approvals and specifications please refer to the Appendix.



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Tubing and Sleeves category:

Click to view products by Hellermann manufacturer:

Other Similar products are found below:

770-006S102 5685710001 CR8248-000 CR9960-000 603312-4 607381P039 611112-000 617867N001 6500750004 CZ1420-000 D-306-38 770-003S106W2 770-005S105W1 770-005S106W1 770-007A303 770-010Y106W1 770-010Y706W1 7771210001 MFP-1/4"-Clear MFP-3/64"-Clear 790-3012 MFT-MT2000-NO.14-0-SP MHHT-4-15K2-G-104 MIL-LT-1/2-4-SP MIL-LT-1/2-9-STK MIL-LT-1/2-2-STK MIL-LT-3/0-SP MIL-LT-3/32-0-SP MIL-LT-3/32-6-SP MIL-LT-3/4-6-SP MIL-LT-3/8-0-SP 8159270001 839602-000 8423-6 FP301-116-6"-Black FP301-1/2-48"-Black FP301-12-48"-Black-Hdr FP301-1/4-48"-Black FP301-1/4-48"-White-Hdr FP301-18-48"-Black-Hdr FP301-1/8-6"-Black FP301-18-6"-Black FP301-316-48"-Blue-Hdr FP301-316-6"-Clear FP301-332-6"-Black 912229N002 120-126-16BL 121-001-09 121-018-32 121-018-32 121-018-40