

This document was generated on 12/10/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 39-30-6227

Status: **Active**

Mini-Fit Jr.™ Power Connectors **Overview:**

Mini-Fit® Jr. Header, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 22 **Description:**

Circuits, PA Polyamide Nylon 6/6, UL 94V-2, Tin (Sn) Over Nickel (Ni) Plating, with

Drain Holes

Documents:

3D Model Test Summary TS-5556-002 (PDF) RoHS Certificate of Compliance (PDF) Drawing (PDF)

Product Specification PS-5556-001 (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series 5566

Application Power, Wire-to-Board

Comments The 5566 header should be used with standard Mini-

4.20mm

Fit® female terminals. If increased amperage of up to 13A per circuit is needed, please consider using the Mini-Fit® Plus HCS family 45750 terminals with 46015 headers; . See Molex Product specification PS-5666-001 for current de-rating information.


Mini-Fit Jr.™ Power Connectors Overview

Product Name Mini-Fit Jr.™ **UPC** 822350910538

Physical

Pitch - Termination Interface

Breakaway No Circuits (Loaded) 22 Circuits (maximum) 22 Color - Resin Natural Durability (mating cycles max) 30 First Mate / Last Break No Flammability 94V-2 Glow-Wire Compliant No Guide to Mating Part No Keying to Mating Part None Lock to Mating Part Yes Material - Metal **Brass** Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Nylon Net Weight 4.518/a Number of Rows 2 Orientation Vertical PC Tail Length 3.50mm **PCB** Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Tray Pitch - Mating Interface 4.20mm



EU RoHS ELV and RoHS Compliant **REACH SVHC Contains SVHC: No Low-Halogen Status** Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series

5566 Series

Mates With

5557 Mini-Fit Jr.™ Receptacle Housing

Polarized to Mating Part

Polarized to PCB

Shrouded

Stackable

No

Surface Mount Compatible (SMC)

Yes

Yes

Yes

No

No

Temperature Range - Operating -40°C to +105°C Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 9A Voltage - Maximum 600V

Solder Process Data

Duration at Max. Process Temperature (seconds) 5

Lead-free Process Capability Wave Capable (TH only)

Max. Cycles at Max. Process Temperature 1
Process Temperature max. C 235

Material Info

Old Part Number 5566-22B2S

Reference - Drawing Numbers

Product Specification PS-5556-001, RPS-5556-004

Sales Drawing SDA-5566-N*2*-* Test Summary TS-5556-002

This document was generated on 12/10/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 891-007-9SS-BST1T 000-34000 0008550134 0009482033 0009507031 57102-F02-18ULF 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 CSU011177004 636-1427 638009-1 641938-9 641991-4 644168-1 644827-2 647662-1 65039-019ELF 65692-001LF 65781-018 65781-047