


Specifications:

Contact rating: 2A, 36V DC; 3A, 125V AC
 Contact resistance: 50mOhm max.
 Insulation resistance: 1000MOhm min. at 500V DC
 Dielectric strength: 1500V RMS (50/60Hz)
 Operating temperature: -40°C to +85°C
 Electrical life: 200 000 cycles
 Operating force: 4N max.
 Switching function: off - mom
 Torque: 5-14Nm max. applied to nut
 IP class: IP65 protection
 IK class: 08
 Travel: 1.5 +/-0.2mm

Material:
 Bushing / button: nickel plated brass
 with varnished polished
 Contact: silver alloy
 Nut: nickel plated brass
 Base: PBT

CONTACT CONFIGURATION



| | | |
|--|-------|------|
| Tolerances:0.00 to 30.00: ±0.20mm 30.01 to 80.00: ±0.25mm | Date | Name |
| | 01/11 | dr |
| | | |
| | | |
| | | |
| Specifications | 02/12 | dr |
| Operating temperature | 05/11 | dr |
| Modifications | Date | Name |

MAV01B3M3F

knitter-switch

30 22 79

Page
1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[LW1L-M1C10V-A](#) [LW2L-A1C20M-GD](#) [LW2L-M1C20M-A](#) [60324L](#) [M7E-HRN2](#) [67021K512](#) [67081K512X](#) [701PB580](#) [719-5504-000](#)
[MDPSSGLFS](#) [810KSV30B](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8646AB6X718UL](#) [8646ABUL](#)
[FSDWH](#) [9001KXRK](#) [9001T8BK](#) [9533CD4+U574+U4922](#) [1203MRA](#) [A22EM01S](#) [A595](#) [1202A6](#) [12037A2ULCSA](#) [1203A2UL](#) [ABD122N-](#)
[B](#) [1211390004](#) [ABN111-Y](#) [ABN400-R](#) [1211500044](#) [1211580012](#) [1212MRA](#) [1232A6NF](#) [RA3CSH6A](#) [1241.1183.7047](#) [1241.2511](#)
[1241.3428](#) [1223A2ULCSA](#) [1223MRA](#) [1232AX2119](#) [1241.1183.8000](#) [1241.1183.8029](#) [1241.2506](#) [1241.2606](#) [12MA6](#) [1301940184](#)
[RELBARF6X10\(PLASTIC\)](#) [13435AG](#)