



Specifications

Rated Current/Voltage(UL)	16A/300V
Rated Current/Voltage(IEC)	17.5A/250V
Contact Resistance	20mΩ Max
Insulation Resistance	500MΩ/DC500V
Wire Range	22-14 AWG 1.5mm ²
Withstanding Voltage	AC 2000V/1Min
Operating Temperature	-40°C ~ +120°C
MAX Soldering	+250°C For 5 Seconds
Torque	0.5Nm(4.5 lb.in)
Strip Length	4.5 - 5mm
Pitch	7.50mm
Number Of Poles	2 -24 Pin

Materials

Housing	PA66, UL94 V-0
Screw	M3.0 Steel Zn Plated
Pin Housing	Brass, Tin Plated
Clamp	Phosphor Bronze, Ni Plated

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [Ninigi](#) manufacturer:

Other Similar products are found below :

[57.404.7553](#) [57.504.0053.7](#) [57.510.0053](#) [57.910.6153](#) [01.112.1453](#) [CTB932VE/6](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [734-104](#) [734-302](#) [734-304](#) [8-141-P](#) [FKCT 2.5/ 3-ST KMGY](#) [860505](#) [860508](#) [860516](#) [860810](#) [861908](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP02-5,00](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [H-10](#) [1546228-5](#) [ELFH09150](#) [ELFH16150](#) [ELFP03110](#) [ELFT06250](#) [ELFT07250](#) [ELVF09400](#) [ELVP03100](#) [ELXH03100](#) [ELXH071G0E](#) [ELXP041G0](#) [ELXT046G0](#) [1700101](#) [1700410](#) [1700425](#) [1703176](#) [1705229](#) [1710175](#) [1714537](#) [1717806](#) [1719600](#) [1729386](#) [1734692](#) [1734795](#)