

OK International Ltd • Eagle Close • Chandler's Ford • Eastleigh • Hants SO53 4NF • UK Phone: +44 (0)1703 489000 • Fax: +44 (0)1703 489109 www.okinternational.com

ETFE-INSULATION (TEFZEL)

1. Structure, Electric, Thermal and Mechanical Values

Copper Wire – Tin Plated Insulation from ETFE – extruded, lightly fixed.

AWG Gauge	30	28	26	24	22
a) Conductor -diameter in mm	0.25	0.32	0.4	0.5	0.63
b) Wall Thickness in mm			0.15		
c) Outside-diameter in mm	0.56	0.63	0.71	0.81	0.94
d) Tolerances in mm			0.05 + or -		
e) Conductor-resistance per kilometer	365	227	143	89.4	56
f) Operating Voltage			max. 375V 50Hz		
g) Testing Voltage			1500V 50Hz		
h) Continuous Operating Temperature			minus 90 to plus 150 deg C		
i) Tensile Strength			30 N/mm2		
k) Elongation of Isolation			150%		
I) Elongation of Conductor		min.15%		max. 20%	
m) Current Capacity in A at 55 degC	2.6	3.4	4.5	5.2	5.7
Ambient Temperature					
n) Colour			10 Standard Colours available		
o) Isolation			Resistance at all diameters min. 3000 Mohm x km		

- 1. These wire connections are suitable for self cutting and stripping tools.
- 2. Tested for VDE 0881
- * AWG = American Wire Gauge

Limited colour variations are permissible in manufacture, so long as there is no possibility of confusion with other colours.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Specialised Cables category:

Click to view products by OK Industries manufacturer:

Other Similar products are found below:

GP-IE515546DS-002 96CB-L2020PIB2 1200740161 R7ACAB003S R88ACAKA0015SRE R88ACAWL005SDE R88ACRGB010C

R88ACRGD0R3C R88ACRGD0R3CBS R88ACRKA020CRE 1300660201 1971465-2 22733-8 2R7004A20F060 SSL009PC2DC012N

FC2A-KC6C FZVS415M CCSFCBF2 R7ACAB005S R88ACAGD003SRE R88ACAGE005BRE R88ACAKE003SRE R88ACAKE005SRE

R88ACAKE010SRE R88ACRKM010SRE R88AFIK222RE XS2WM12PUR4SA10M XS2WM12PVC4SA10M 05AU05 UCABLE

10114734-2010LF R88ACRKC015NRE XW2Z010H3 XW2Z010H1 5-1589827-8 861084-1 XW2Z200JB24 CR4000A76M020

1300140039 CR4000A76M005 CR4006A76M005 10077488-N0550FDLF XW2ZRY150C I4JPBJLUXX100 I4JPBJLUXX50 CM06W

CM08 POE004 0243 009 05 0243 009 20