

High Temperature IR Thermometer

Measures surface temperature up to 1400°F (760°C)

With built-in Laser Pointer that identifies target area and improves aim

Features:

- √ High temperature range from -58° to 1400°F (-50 to 760°C)
- √16 to 1 distance to target ratio measures smaller surface areas at greater distances
- ✓Adjustable high/low alarm alerts user visually and audibly when temperature exceeds programmed limits
- √Adjustable emissivity for better accuracy on different surfaces
- ✓MAX/MIN/AVG/DIF features display highest, lowest, average, and MAX minus MIN values
- Large backlit display
- · Laser pointer identifies target area
- · Automatic Data Hold
- · Automatic Power Off
- High Resolution of 0.1° up to 199.9°
- · Complete with 9V battery and hard carrying case



Laser pointer identifies target area.



Includes either soft or hard carrying case

Ordering Information:

42540	High Temperature IR Thermometer
42540-NIST	42540 with NIST Certificate



Specifications	
Range	-58 to 1400°F (-50 to 760°C)
Basic Accuracy	±2%rdg or 4°F (2°C) <932°F (500°C); ±(2.5%rdg + 5°)>932°F (500°C)
Max. Resolution	0.1°F/°C
Emissivity	0.1 to 1.00 Adjustable
Field of View (Distance to Target)	16:1
Dimensions	3.9 x 2.2 x 9" (100 x 56 x 230mm)
Weight	10.2oz (290g)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160