<u>TOSHIBA</u>

TOSHIBA Photocoupler GaA{As Ired + Photo-IC

TLP759F

Digital Logic Ground Isolation Line Receiver Microprocessor System Interfaces Switching Power Supply Feedback Control Transistor Inverter

The TOSHIBA TLP759F consists of a GaAlAs high-output light emitting diode and a high speed detector of one chip photo diode-transistor. This unit is 8-lead DIP package.

TLP759F has no internal base connection, and a Faraday shield integrated on the photodetector chip provides an effective common mode noise transient immunity.

So this is suitable for application in noisy environmental condition. All parameters are tested to the specification of TLP759.

- Isolation voltage: 5000 Vrms (min)
- Switching speed: $t_{pHL} = 0.2 \ \mu s \ (typ.)$ $t_{pHL} = 0.3 \ \mu s \ (typ.) \ (R_L = 1.9 \ k\Omega)$
- TTL compatible
- UL recognized: UL1577, file no. E67349
- BSI approved: BS EN60065:2002, certificate no.8869 BS EN60950-1:2002, certificate no.8870
- Option (D4) type VDE approved: DIN EN 60747-5-2

Certificate no. 40009302 Maximum operating insulation: 1140V_{PK} Highest permissible over voltage: 6000V_{PK}

(Note) When an EN 60747-5-2 approved type is needed, please designate the "Option (D4)"

• Creepage distance: 8.0 mm Clearance: 8.0 mm Insulation thickness: 0.4 mm



Weight: 0.54 g (typ.)

Pin Configuration(top view)



Schematic



Start of commercial production 1995/08

RESTRICTIONS ON PRODUCT USE

- Toshiba Corporation, and its subsidiaries and affiliates (collectively "TOSHIBA"), reserve the right to make changes to the information in this document, and related hardware, software and systems (collectively "Product") without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before creating and producing designs and using, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application that Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.
- Product is intended for use in general electronics applications (e.g., computers, personal equipment, office equipment, measuring equipment, industrial robots and home electronics appliances) or for specific applications as expressly stated in this document. Product is neither intended nor warranted for use in equipment or systems that require extraordinarily high levels of quality and/or reliability and/or a malfunction or failure of which may cause loss of human life, bodily injury, serious property damage or serious public impact ("Unintended Use"). Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. Do not use Product for Unintended Use unless specifically permitted in this document.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any
 applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.
- GaAs (Gallium Arsenide) is used in Product. GaAs is harmful to humans if consumed or absorbed, whether in the form of dust or vapor. Handle with care and do not break, cut, crush, grind, dissolve chemically or otherwise expose GaAs in Product.
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. TOSHIBA assumes no liability for damages or losses occurring as a result of noncompliance with applicable laws and regulations.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MOSFET Output Optocouplers category:

Click to view products by Toshiba manufacturer:

Other Similar products are found below :

 TLP3131(F)
 TLP598GAF
 CPC2014NTR
 TLP4026G(F)
 LTV-817S-B
 CPC2017NTR
 TLP152(TPL,E(T)
 PS2505L-4-E3-A
 TLP3106A(TP,F)

 TLP3107A(F)
 TLP3106A(F)
 TLP3149(F)
 TLP3145(F)
 TLP3146(F)
 TLP3149(TP,F)
 H11AV1XSM
 CNY17-1-000E

 CNY17-1-300E
 CNY17-1S
 CNY17-2-000E
 CNY17-2S
 CNY173SR2VM
 CNY17-4-000E
 HCPL-181-06DE
 HCPL-J312-000E
 LTV-3120S

 TA1
 LTV-817-L
 LTV-817S-A
 LTV-817S-TA1-L
 TIL111
 TIL191
 MCT6X
 MCT6XSM
 TLP170A(F)
 TLP170G(F)

 TLP197GA(F)
 TLP197G(TP,F)
 TLP222A-2(LF1,F)
 TLP291(GR-TP.E(O)
 TLP797J(F)
 4N35X
 4N35XSM
 MOC213M

 HMHA2801R2
 ILD1XSM
 ILQ2X
 ILQ2X
 ILD1XSM
 ILQ2X