

1.27mm(.050") Pitch


Electric & Physical Characteristic:

- | | |
|----------------------------------|--|
| 1. Voltage Rating | :300V |
| 2. Temperature Rating | :105°C |
| 3. Dielectric Strength | :2. OKV 60Hz 1 Minute
(No Break Down) |
| 4. Conductor Resistance | : 237 /KM Max. |
| 5. Insulation Resistance | :100M /M Min. at DC
500V |
| 6. Tensile Strength Before Aging | :1500PSI |
| Tensile Strength After Aging | :70% MIN. (136°C*168H) |
| 7. Elongation Before Aging | :100% MIN. |
| Elongation After Aging | :65% MIN. (136°C*168H) |
| 8. Deformation Test | :50% Max. (121°C*1H) |
| 9. Cold Bend Test | :-10°C*4H No Cracking |
| 10. Horizontal Flame Test | :VW-1 |

Note:

Cable is RoHS Compliant


No. of conductor	Width (mm)	Composition (mm)	Allowable error
9P	11.43	7/0.127	± 0.30
10P	12.7	7/0.127	± 0.30
15P	19.05	7/0.127	± 0.30
16P	20.32	7/0.127	± 0.30
20P	25.4	7/0.127	± 0.30
24P	30.48	7/0.127	± 0.30
25P	31.75	7/0.127	± 0.40
26P	33.02	7/0.127	± 0.40
34P	43.18	7/0.127	± 0.40
37P	46.99	7/0.127	± 0.40
40P	50.80	7/0.127	± 0.40
44P	55.88	7/0.127	± 0.40
50P	63.50	7/0.127	± 0.40
60P	76.20	7/0.127	± 0.40
64P	81.28	7/0.127	± 0.40



$n \leq 30$
 $a = \pm 0.30$
 $n \geq 31$
 $a = \pm 0.40$

(N=Number of Conductors)

How to Order



RoHS
Compliant

ITEM NO
AWG28-XX/X/300

TITLE
Flat Ribbon Cable, 1.27mm Pitch
300 Feet, 13" Reel, (Gray & Multi-Color)

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 – Tempe, AZ 85283

Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
© Copyright 2008 by Assmann Electronic Components
All International Rights Reserved

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ribbon Cables / IDC Cables](#) category:

Click to view products by [Assmann](#) manufacturer:

Other Similar products are found below :

[FSK-12A Ribbon Cable, 6 Pin, 500mm](#) [AWG28-10G EHV3C EHV4C EHV5C](#) [cab-LVDV-PWR-10-15 FSP-25A Ribbon Cable, 4 Pin, 350mm](#)
[Ribbon Cable, 6 Pin, 300mm](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [92315-1408](#) [100063-0094](#) [100063-0106](#) [100063-0102](#)
[100063-0104](#) [MMSD-02-20C-F-15.00-S-K](#) [100063-0099](#) [100063-0105](#) [100063-0095](#) [100063-0103](#) [100063-0093](#) [100063-0091](#) [2200000068](#)
[100063-0092](#) [100063-0101](#) [100063-0100](#) [100063-0097](#) [TFSDT-08-28-H-15.00-S](#) [S1SD-02-30-GF-09.00-L](#) [MMSD-02-22C-F-15.00-S-K](#)
[S1SS-02-28C-GF-02.00-L](#) [S1SDT-02-28-GF-03.00-L](#) [2-1589735-3](#) [JSM015PP2DCC23N](#) [92301-0283](#) [TCSD-22-D-26.00-01](#) [S1SST-07-30-](#)
[GF-06.00-L](#) [T2SD-20-24-L-07.87-TR-NUS](#) [DS1057-01-44A282R-30.5](#) [FFSD-06-S-17.00-01-N](#) [IDSS-03-D-20.00-T](#) [TCMD-17-S-36.00-01-](#)
[SR](#) [92301-0718](#) [839023](#) [490107670612S](#) [MMSDT-06-20-S-05.5-D-K-LDX](#) [IDD-04-G](#)