



**TSH, TMMS SERIES**

**(2,00 mm) .0787"**

# SHROUDED HEADERS

**Mates with:**

CLT, SQT, SQW, ESQT, TLE, SMM, MMS, PTF

**SPECIFICATIONS**

For complete specifications and recommended PCB layouts see [www.samtec.com?TSH](http://www.samtec.com?TSH)

**Insulator Material:** Black Liquid Crystal Polymer  
**Terminal Material:** Phosphor Bronze

**Plating:** Sn or Au over 50µ" (1,27 µm) Ni

**Operating Temp Range:** -55°C to +105°C with Tin; -55°C to +125°C with Gold  
**RoHS Compliant:** Yes

**Processing:**

**Lead-Free Solderable:** Yes  
**SMT Lead Coplanarity:** (0,15 mm) .006" max

**RECOGNITIONS**

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



**Note:** Some lengths, styles and options are non-standard, non-returnable.

<b>TSH</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>01</b>	<b>PLATING OPTION</b>	<b>ROW OPTION</b>	<b>OTHER OPTION</b>
		<b>05, 10, 15, 20, 25, 30, 35, 40, 45</b> (40 & 45 = -D & -RA only) (Standard sizes)		<b>-F</b> = Gold flash on post, Matte Tin on tail <b>-L</b> = 10µ" (0,25 µm) Gold on post, Matte Tin on tail <b>-T</b> = Matte Tin	<b>-D</b> = Vertical Through-Hole <b>-DV</b> = Vertical Surface Mount <b>-RA</b> = Right Angle Through-Hole <b>-DH</b> = Horizontal Surface Mount	<b>-LC</b> = Locking Clip (-DV only) (N/A with -A) (Manual placement required) <b>-A</b> = Alignment Pin (-DV only) (N/A with -LC) <b>-SL</b> = Solder Locks (-DH only) <b>-K</b> = (4,50 mm) .177" DIA Polyimide Film Pick & Place Pad (N/A with 15 - 30 positions) (-DH only) <b>-M</b> = Metal Pick & Place Pad (-DV only) (N/A -T plating) <b>-TR</b> = Tape & Reel

**ALSO AVAILABLE**  
(MOQ Required)

- Other sizes and platings

Contact Samtec.

**Mates with:** SQT, SQW, ESQT

**SPECIFICATIONS**

For complete specifications see [www.samtec.com?TMMS](http://www.samtec.com?TMMS)

**Insulator Material:** Black LCP  
**Terminal Material:** Phosphor Bronze

**Plating:** Sn or Au over 50µ" (1,27 µm) Ni

**Operating Temp Range:** -55°C to +105°C with Tin; -55°C to +125°C with Gold  
**RoHS Compliant:** Yes

**Lead-Free Solderable:** Yes

**RECOGNITIONS**

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



**Note:** Some lengths, styles and options are non-standard, non-returnable.

<b>TMMS</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>01</b>	<b>PLATING OPTION</b>	<b>Q</b>	<b>OPTION</b>	<b>FS</b>
		<b>05, 10, 15, 20, 30, 40, 50</b>		<b>-F</b> = Gold flash on post, Matte Tin on tail <b>-L</b> = 10µ" (0,25 µm) Gold on post, Matte Tin on tail		<b>-RA</b> = Right Angle	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Samtec](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [009176003701906](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#)