




Note:


Material : Brass Finish : Tin plated Thickness : 0.2mm

Applicable wires : AWG#18~24











TOLERANCE (mm)		APPROVALS	DATE	TITLE	AMPHENOL	
X.	±0.3	Stephane	05/Jan/2007	4.2 Power Contact	Amphenol European	
xx	±0.2	Rob	05/Jan/2007	Male for Housing	Design Center	
x.xx	±0.15	APPROVED Rob	05/Jan/2007	male for Flodeling	Scale N.A.	Sheet 1 of 1
UNLESS OTHERWISE SPECIFIED			mm	SIZE: DRAWING N' MF42-HM	PRAWING N' MF42-HMT	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

571763P 58098-0628 61-168618-12P D38999/20FJ29SB L/C 72.250.1628.2 72.250.2428.2 74720-0505 747680210 76.350.0729.0 768711403 FCN-244F080-G/1 FCN-260A9920 FCN-268D024-G/2F#10X-R10 MP-5T180MUNNA-005 MP-5XRJ45UNNB-003 PCS-E50FA
PCS-XE26LKA PCS-XE26MA+ PCS-XES68MS+ G38A71314B 91-569719-35R 9776-18-6 DX40-50P(55) 1571250010 157-22500-3
MS3471L14-19P L/C 171224-6031 1888020-8 91-569786-35H 91-569786-35M 91-644626-35P 172501-4002 172501-6002 FCN-260C008A/L0 FCN-260C024-AL0 FCN-261Z008 FCN-268D008-G/1K 2000314-1 200331-1 2007498-2 PCR-E28LMDAG1+ PCR-E36FC+ PCSE28FS+ PCS-XE26SLFD+ PCS-XE26SLFDT+ G38A71214B HDRA-E68W1LFDTC-SL+ HDR-E14MSG1+ R88A-CNK81S CRT1ATT02