



HELUKABEL SUPERTRONIC-PVC 4x0,25 QMM / 49563 350 V 001041714

CE



Technical data

- Special PVC cable for drag chains, adapted to DIN VDE 0285-525-1 / DIN EN 50525-1
- Very high flexible due to special construction
- **Temperature range**
flexing -5°C to +70°C
fixed installation -40°C to +70°C
- **Nominal voltage** 350 V
- **Test voltage** 1500 V
- **Breakdown voltage** min. 3000 V
- **Insulation resistance**
min. 20 MOhm x km
- **Minimum bending radius**
flexing 5x cable Ø
fixed installation 3x cable Ø
- **Radiation resistance**
up to 80x10⁵ cJ/kg (up to 80 Mrad)

Cable structure

- Bare copper, extra fine wire conductors, to DIN VDE 0295 cl.6
- Core insulation of special PVC compound type T12 to DIN VDE 0207-363-3 / DIN EN 50363-3
- Cores colour coded to DIN 47100, see Technical Informations
- Cores stranded in layers with optimal selected lay-length
- Core wrapping with textile tape
- Outer sheath of special PVC compound type TM2 to DIN VDE 0207-363-4-1/DIN EN 50363-4-1
- Colour grey (RAL 7001)
- with meter marking

Properties

- Extensively oil resistant
Chemical Resistance - see table Technical Informations
- Adhesion-low
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Tests

- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)

Note

- AWG sizes are approximate equivalent values. The actual cross-section is in mm².

Application

The ideal cable for use in cable trays. This high flexible cable is ideal for all areas requiring a high and fast flexing cable including the machine industries, robotics and all areas of highly mobile machine parts. The long working life offers a secure performance as well as economy. For applications which go beyond standard solutions (for example for composting appliances or high shelf conveyors with extremely high processing speeds etc.) we recommend for our especially developed enquiry sheet for energy guiding systems. Before installation in cable trays please read the instructions. Further technical details see selection table for drag chain cables, see lead text.

CE = The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
49550	2 x 0,14	3,5	2,8	23,0	26
49551	3 x 0,14	3,7	4,1	25,0	26
49552	4 x 0,14	3,9	5,6	30,0	26
49553	5 x 0,14	4,2	7,0	35,0	26
49554	7 x 0,14	4,8	9,8	49,0	26
49555	10 x 0,14	6,2	14,0	64,0	26
49556	12 x 0,14	6,3	16,8	71,0	26
49557	14 x 0,14	6,6	19,6	77,0	26
49558	18 x 0,14	7,2	25,2	90,0	26
49559	24 x 0,14	8,5	33,6	119,0	26
49560	25 x 0,14	8,6	35,0	124,0	26
49561	2 x 0,25	4,2	5,0	28,0	24
49562	3 x 0,25	4,4	7,5	33,0	24
49563	4 x 0,25	4,7	10,0	39,0	24
49564	5 x 0,25	5,6	12,5	50,0	24
49565	7 x 0,25	6,1	17,5	63,0	24
49566	10 x 0,25	7,2	25,0	83,0	24

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
49567	12 x 0,25	7,5	30,1	95,0	24
49568	14 x 0,25	7,9	35,0	107,0	24
49569	18 x 0,25	8,9	45,0	130,0	24
49570	24 x 0,25	10,4	60,0	170,0	24
49571	25 x 0,25	10,5	62,5	177,0	24
49572	2 x 0,34	4,6	6,8	33,0	22
49573	3 x 0,34	4,8	10,2	42,0	22
49574	4 x 0,34	5,2	13,6	56,0	22
49575	5 x 0,34	6,1	17,0	64,0	22
49576	7 x 0,34	7,0	23,8	84,0	22
49577	10 x 0,34	8,4	34,0	116,0	22
49578	12 x 0,34	8,5	40,8	133,0	22
49579	14 x 0,34	9,0	47,6	150,0	22
49580	18 x 0,34	10,1	61,2	182,0	22
49581	24 x 0,34	12,0	81,5	240,0	22
49582	25 x 0,34	12,2	85,0	250,0	22

Dimensions and specifications may be changed without prior notice. (RC03)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Paired Cables](#) category:

Click to view products by [Helukabel](#) manufacturer:

Other Similar products are found below :

[7-21000-9](#) [9805 060100](#) [1416402/M12MS/IP20/10](#) [9804 060100](#) [9808 060100](#) [9843 060100](#) [9873 060100](#) [190-038045-00](#) [44A0121-12-996CS2275](#)
[44A0121-20-09-MX](#) [55PC0211-14-9](#) [55PC0216-24-9](#) [55PC0221-22-2/6CS2756](#) [55PC0811-16-9](#) [55PC0811-24-9](#) [55PC1131-20-029-9](#) [Y60912](#)
[CW1922-000](#) [RI55D](#) [9157 060100](#) [2020D0309-0](#) [9774 060100](#) [8334 060100](#) [1350SB 0101000](#) [8342 060100](#) [8740 060U1000](#) [9505 060U1000](#)
[3613 003A1000](#) [44A0121-22-0/9-MX](#) [2412 009U1000](#) [82777 8771000](#) [9406 T35100](#) [3613 D151000](#) [1533R 0101000](#) [1533P 0101000](#) [9272](#)
[006U1000](#) [2413F D15A500](#) [9681 0601000](#) [44A0121-22-6/9-MX](#) [1533R 0061000](#) [RIT1000](#) [1533R 006A1000](#) [9812 060100](#) [2221 B59U1000](#)
[10GX13 D151000](#) [1874A 004A1000](#) [8340 060100](#) [8333 0601000](#) [1533R 0021000](#) [1583A 012U1000](#)