



FEATURES:

- Breakout quickly converts a BNC cable to flying leads
- Lead ends can be attached to terminal strips or customized
- BNC connector is molded directly to the wire for pull strength durability and dust and moisture resistance
- BNC center contact is gold plated Beryllium Copper for corrosion resistance, low contact resistance and long insertion life
- Black lead is connected to BNC shell, red lead to BNC center contact

MATERIALS:

BNC: Nickel plated brass

Center Contact: Gold plated Beryllium Copper

Wire: 20 AWG, PVC

Marking: "POMONA 4969" or "POMONA 4970"

RATINGS:

Operating Voltage: 500 VRMS

Operating Temperature: +55°C (+131°F) Max.

ORDERING INFORMATION: Model 4969 or 4970

BNC breakouts with banana plugs, spade lugs, alligators and Minigrabber test clips are also available

*Custom lengths are available, contact Pomona Technical support: 800-241-2060 (Technicalsupport@pomonatest.com)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [leviton](#) manufacturer:

Other Similar products are found below :

[9800](#) [OSC10-RMW](#) [OSFHU-ITW](#) [16S31-R](#) [41089-2WP](#) [5100-PS](#) [41108-RW5](#) [X7599-HGW](#) [10032-200](#) [66593-3](#) [8598-HGW](#) [8898-HGW](#)
[2611](#) [1203-PLG](#) [4716-CWP](#) [N1303](#) [2713-B](#) [2811](#) [2813](#) [2815](#) [5266-CY](#) [16R22-W](#) [2711](#) [5997-CL](#) [16D22-Y](#) [16D31-B](#) [2713](#) [5266-C](#)
[5G108-RT5](#) [7314-C](#) [9650-P](#) [6674-P0W](#) [16D22-UE](#) [16R27-UR](#) [16R27-UE](#) [9452-P](#) [5256-VY](#) [15378-CWP](#) [OSFHP-ILW](#) [16D31-E](#) [2310](#)
[2525](#) [9840](#) [T5632-T](#) [16R28-UE](#) [16S31-B](#) [2711-B](#) [41020-SPR](#) [5262-IG](#) [1547](#)