Multifunction time ralay TRAh-C



www.mikrobest.pl

Multifunction time ralay. Multiscale. Multivoltage. 1 relay output DPDT



General characteristics

- Electronic time relay, multiscale, multivoltage.
- 1 relay output with 2 changeover contact (DPDT)
- Green LED indicator for relay state
- Modular DIN 35mm

Order code	Time of scale range	Rated auxiliary supply voltage	Qty per pkg
TRAm-C	12s-12h	v	1
		24 V AC/DC 230 V AC	

Function

On delay (Power on)

When the input voltage U is applied,timing delay t begins.
Relay contacts R change state after time delay is complete.
Contacts R return to their shelf state when input voltage U is removed.

Interval (Power off)
When the input voltage U is applied, relay contacts R change state.
immediately and timing cycle begins.
When the time delay is compete, contacts return to shelf state.
When input voltage U is removed, contacts will also return to their shelfstate.


Repeat Cycle(Starting off))
When the input voltage U is applied time delay t begins.
When time delay t is comlete, relay contacts R change


state for time delay t.

This cycle will repeat until input voltage U is removed.

Repeat Cycle(Starting on)
When the input voltage U is applied, relay contacts R change

state immediately and time delay t begins.
When the time delay t is complete, contacts return their shelf state for time delay t.
This cycle will repeat until input voltage U is removed.






Time rangers

x₁h

x8m

x₁m

x15s



Technical parameters

Supply terminals: A1 - A2 230VAC


C1 - A2 24V AC/DC

Supply voltage tolerance: 0,8 - 1,1 % Consumption: max 8VA 8A/250V AC1 Current rating:

8A/24V DC1

Time deviation: 5% Protection degree: IP20

Dimensions: 90 x 35 x 45mm



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Timers category:

Click to view products by Mikrobest manufacturer:

Other Similar products are found below:

79237785 H3DS-GL AC24-230/DC24-48 H5AN-4DM DC12-24 H5CN-XDNM AC100-240 H5CN-YAN AC100-240 H5CX-L8S-N AC100-240 H3AMNSCAC100240 H3AM-NSR-B AC100-240 H3CA-8 DC12 H3CR-A8-302 DC24 H3CR-F AC24-48/DC12-48 H3CR-G8EL AC200-240 H5AN-4D DC12-24 81506944 88225029 H5S-YB4-X H3CR-A-301 AC100-240/DC100-125 H3CR-AS AC24-48/DC12-48 H3DK-GE AC240-440 H3RN-2 AC24 H3RN-21 AC24 H3CR-H8RL AC/DC24 M H3CR-H8RL AC100-120 S H3CR-G8EL-31 AC100-120 H3CR-H8RL AC100-120 M H3CR-A8-301 AC24-48/DC12-48 H3CR-H8RL AC/DC24 S H7AN-2D DC12-24 H5CN-XANS DC12-48 H3CA-8 DC110 H7AN-W4DM DC12-24 H7AN-4DM DC12-24 H7AN-4D DC12-24 H7AN-RT6M AC100-240 H3CA-8H AC200/220/240 MTR17-BA-U240-116 PM4HSDM-S-AC240VS PM4HSDM-S-AC240VSW PO-405 600DT-CU H3Y-2-B DC24 30S PM4HF8-M-DC24V PM4HS-H-DC12VSW H3Y-2-B AC100-120 10S H3Y-2-B AC100-120 30S H3C-R H3CR-A8-301 24-48AC/12-48DC H3CR-A8E 24-48AC/DC H3CR-F8 100-240AC/100-125DC