


P.C. MOUNTING



SWITCH FUNCTION

Model No.	POS. 1	POS. 2
		OFF
TSP 1 C	OFF	MOM
Term. Conn.	-	1-3

Specifications:

- Contact rating: 0.4VA max., 20V max. (AC or DC)
- Contact resistance: 20mOhm max. at 2-4V DC
- Insulation resistance: 1 000MOhm min.
- Dielectric strength: 1 000V RMS
- Operating temperature: -30°C to +85°C
- Mechanical life: 50 000 make-and-break cycles
- Soldering conditions: 260 +/-5°C, 5 +/-1sec.
- IP rating: IP67
- Material: Case / bushing: glass filled nylon 66, flame retardand, heat stabilized (UL94V-0)  
Plunger: thermoplastic polyester (UL94V-0)  
Switch support: brass, tin plated  
Contact: gold plated copper alloy



Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm		Date	Name	<h1>TSP 1 C</h1>
		09/08	dr	
			<b>knitter-switch</b>	<h2>30 15 95</h2>
IP rating	04/12	dr		
Modifications	Date	Name		

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [Knitter-Switch](#) manufacturer:*

Other Similar products are found below :

[LW1L-M1C10V-A](#) [LW2L-A1C20M-GD](#) [LW2L-M1C20M-A](#) [60324L](#) [M7E-HRN2](#) [67021K512](#) [67081K512X](#) [701PB580](#) [719-5504-000](#)  
[MDPSSGLFS](#) [810KSV30B](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8646AB6X718UL](#) [8646ABUL](#)  
[FSDWH](#) [9001KXRK](#) [9001T8BK](#) [9533CD4+U574+U4922](#) [1203MRA](#) [A22EM01S](#) [A595](#) [1202A6](#) [12037A2ULCSA](#) [1203A2UL](#) [ABD122N-](#)  
[B](#) [1211390004](#) [ABN111-Y](#) [ABN400-R](#) [1211500044](#) [1211580012](#) [1212MRA](#) [1232A6NF](#) [RA3CSH6A](#) [1241.1183.7047](#) [1241.2511](#)  
[1241.3428](#) [1223A2ULCSA](#) [1223MRA](#) [1232AX2119](#) [1241.1183.8000](#) [1241.1183.8029](#) [1241.2506](#) [1241.2606](#) [12MA6](#) [1301940184](#)  
[RELBARF6X10\(PLASTIC\)](#) [13435AG](#)