

SKINDICHT® BL-M

SKINDICHT® BL-M, brass blind plugs for closing pre-threaded holes, assembling with screwdriver



CE



Temperature-resistant



Reliability



Robust



Corrosion-resistant

Benefits

For closing pre-threaded holes
Assembling with screwdriver

Application range

Machine and equipment manufacturing
Electric motor manufacturing

Product Make-up

Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444

Note

Drawing on request

SKINDICHT® BL-M**Technical Data**

Classification:	ETIM 5.0 Class-ID: EC000032 ETIM 5.0 Class-Description: Plug for cable screw gland
On request:	Fitted with FKM O-ring
Material:	Body: nickel-plated brass Sea water-resistant
Protection rating:	IP 54 IP 68 (with O-Ring)
Temperature range:	With O-ring: -30°C to +100°C Without O-ring: -60°C to +200°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Article designation / size	Outer Ø (mm)
SKINDICHT® BL-M		
52103100	M 12 x 1,5	14
52103110	M 16 x 1,5	18
52103120	M 20 x 1,5	22
52103130	M 25 x 1,5	28
52103140	M 32 x 1,5	35
52103150	M 40 x 1,5	44
52103160	M 50 x 1,5	54
52103170	M 63 x 1,5	70
SKINDICHT® BL-M with O-ring		
52103105	M 12 x 1,5	14
52103115	M 16 x 1,5	18
52103125	M 20 x 1,5	22
52103135	M 25 x 1,5	28
52103145	M 32 x 1,5	35
52103155	M 40 x 1,5	44
52103165	M 50 x 1,5	54
52103175	M 63 x 1,5	70
52103190	M 75 x 1,5	80

Last Update (10.07.2017)
 ©2017 Lapp Group - Technical changes reserved
 Product Management www.lappkabel.de
 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03.16

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cable Glands, Strain Reliefs & Cord Grips](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[120-116-1-1-20BP](#) [120-116-1-1-32BE](#) [120-117-40](#) [120-123-14](#) [120-123-16](#) [120-125-16](#) [120-125-16R](#) [120-125-16Y](#) [120-125-24Y](#) [120-125-28](#) [120-125-28R](#) [120-125-32](#) [120-125-32R](#) [120-125-40](#) [120-125-56](#) [120-126-14](#) [120-126-16](#) [120-126-20](#) [120-126-20BL](#) [120-126-20R](#) [120-126-24](#) [120-126-28](#) [120-126-32](#) [120-126-40BL](#) [120-116-1-1-06BP-509](#) [120-116-1-1-06CP](#) [120-116-1-1-16BE](#) [120-116-1-1-28BP](#) [120-123-20](#) [120-123-24](#) [120-123-32](#) [120-125-20](#) [120-125-20Y](#) [120-125-24](#) [120-125-24R](#) [120-125-28Y](#) [120-126-14BL](#) [120-126-16R](#) [120-126-16Y](#) [120-126-24BL](#) [120-126-28BL](#) [120-126-32BL](#) [120-126-40](#) [120-126-48](#) [120-126-48BL](#) [1300980012](#) [1300980105](#) [DBZM-6828](#) [1498](#) [15190-103 R2](#)