Corning New metal Self-Install Compression Connector The perfect choice for Do-It-Yourself and professional

The perfect choice for Do-It-Yourself and professional installations – no special tools required!



The next generation of Cabelcon Self-Install™ is a unique quality product developed for replacement of low quality screw-on connectors - often used for home installations. Installation is easy, simple and more precise than ever before.

Self-Install™ is easy to push on — but impossible to pull off. The connector is automatically fastening to the cable as the connector is installed. It remains fastened — also after dismounting from the unit.

- Operational to 3 GHz
- Waterproof versions available*
- Easy and safe installation in seconds
- One-piece connectors no loose parts
- No compression or special tools needed
- Plated with our unique Nitin-6™ plating
- Unique Self-Install™ compression system
- Professional quality and excellent performance
- Simple instructions can be installed by anyone
- Fits many standard RG6/59 cables (3.9+4.9+5.1+4.9 Q)
 - * An external rubber ring for interface sealing is strongly recommended. Read more on next page.



Installation

- 1) Strip the cable (6.5/6.5 mm) and pull back the braid.
- 2) Press the connector over the cable until the dielectric is flush with the post interface. Pull back the cable.
- 3) Mount the connector/cable on the set-top box and tighten with a standard 11 mm/or adjustable hex wrench. Ready!

Use the Self-Install™ for CATV, satellite receivers, cable modems and other settop box applications. The waterproof versions can be used for any outdoor application such as parabolic dishes etc.



Self-Install ™ with finger friendly nut

Technical Data (Typical)

Operational to 3 GHz **Impedance** 75 Ohm Shielding Eff. 30-862 MHz 110 dB Shielding Eff. 862-3000 MHz 90 dB Transfer Impedance 5-1000 MHz <5 mOhm Return loss@1000 MHz (typ) 37 dB Return loss@3000 MHz (typ) 28 dB IMD (3rd order@2x100mW) -120dBc IMD (IP3 value) +80 dBm AMP rating cable data Max. Tensile strength (overall) 200 N

Detailed datasheets available on request

Ordering information

F-59 3.9 Self-Install Nitin 99909646 F-56 4.9 Self-Install Nitin 99909643-01 F-56 4.9 W Self-Install Nitin 99909647-01 F-56 5.1 Self-Install Nitin 99909645-01 F-56 5.1 Self-Install Nitin 99909644-01 W=Waterproof)



Corning New metal Self-Install[™] compression Connector Cabelcon

waterproof





Easy on - impossible off!

Installation is easy, simple and more precise than ever before. Strip the cable and push on the connector − it's as simple as that. The Cabelcon Self-Install™ connector is automatically fastening to the cable without a compression tool. And you can't get it off! The typical pull strength is better than cable specification.

Self-Install™ - also for professionals

Self-Install™ is also for the professional installer. Both electrical and mechanical connector performance is up to the professional standards. Self-Install™ is available both for indoor and outdoor applications.

Self-Install™ - now also waterproof versions available


The waterproof Self-Install™ is equipped with two EPDM O-rings — one in the body part and one placed behind the nut to prevent moisture intrusion. However, to make sure that the connection is completely waterproof from the interface — we strongly recommend installing an external rubber sealing ring.



- is the perfect companion to go with a couple of Self-Install™ connectors for home installations. The pocket installer combines a RG6/59 cable stripper with mechanical stop for proper stripping length and an 11 mm spanner. The Pocket installer makes the cable preparation much easier and precise, while the spanner can be used for proper tightening.



Computer controlled test of the pull strength





Proper tightening with the Pocket installer

Ordering information

Cable Stripper RG6/59
w/ hex 11 Spanner 98501040
Seal ring for F-connectors 99900902
Seal ring for F-connectors 99900912



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connectors / Coaxial Connectors category:

Click to view products by Cabelcon manufacturer:

Other Similar products are found below:

R125315120 8915-1511-000 89674-0827 5916-1103-603 0106-001-000 6-0001-3 6001-7071-019 6002-7051-003 6002-7551-202 6059674
1 619550-1 630059-000 M39012/25-0021 M39012/79-3008 M39030/3-01N M39030/3-03N M3933/25-29N M3933/25-36N 6500-7071-046

6501-1071-002 M83723/72W24576 M83723/72W2457N 6769 CX050L2AQ 7002-1541-010 7003-1572-002 7004-1512-000 7009-1511
004 7010-1511-000 7029-1511-060 7101-1541-010 7101-1571-002 7105-1521-002 7145-1521-002 7209-1511-011 7210-1511-012 7210
1511-015 7210-1511-019 7210-1511-040 7225-1512-050 7242-1511-000 73137-5015 73216-2241 73251-0111 73251-0672 73276-1501

73366-0013 73404-2300 73413-6080 734151610