

TOROIDAL OUTPUT TRANSFORMER Type TTG-KT88SE Single Ended

TTG-KT88SE Single Ended Output Transformer

Toroidal Single Ended output transformer with UL tap, for tubes KT88, 300B introduces benefits of toroidal cores to tube output. Through the use of innovative, internationally patented winding technology, we have achieved exceptional electrical parameters, such as flat frequency bandwidth in acoustic range, very low THD distortion and high quality factor.

Transformer is also available in stainless steel box potted EXPO version.

Technical Data:

Nominal power: 40W
Nominal anode current: 250mA
Frequency bandwidth (-3dB): 10Hz - 56kHz
Secondary inductance: 4 i 8Ω

Secondary inductance: $4 \text{ i } 8 \Omega$ Primary Impedance: $3,0 \text{ k}\Omega$


Turns Ratio (Np:Ns): $27,39:1 (4\Omega)$, $19,36:1 (8\Omega)$

Primary Inductance Lp: 39,5H Primary Leakage Inductance Lsp: 10,88mH Total Primary DC Resistance: 85,4 Ω


Core type: Toroidal

Intended for: Single Ended, 43% UL

Wiring diagram:







DIMENSIONS:

Outer diameter (D): 115mm
Inner diameter (d): 40mm
Height (h): 65mm
Weight: 2,5 kg
Leeds length: 250mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Transformers category:

Click to view products by Toroidy manufacturer:

Other Similar products are found below:

1-1672275-3 A41-43-20A20 DST5-120B39 14A-56-36B42 EN2997SE61808F8 9-1611461-2 29768 1654308-1 170R ST2-12B42 ST312B5 ST6118T-R PE-68421NL PL2.5-12-130B-C PoE4W3x5.0-R POE7W3X3.3-R 4000-20C02K999 4001-09W15AE777 48RO-5000GSIL TRA-0130-R XON7-15/2 47045010 1-1611462-6 1-1611760-0 EN2997SE61808F9 OPT110F-EAS00004AU XON25-9/24 XON01349

XON01200 XDCA001/INER01 PE-68414NL F-91X F-29U 6673GE DST4-16B10 DP241-8-24A55 DP241-5-10A21 P-8577 T50-24M3
1-1672277-2 1-1672277-0 1-1672275-5 1-1672275-0 4000-01V18BC999 PC-24-180B18 750315837 750315125 POE13W2VERS-R
PA2380NL 14A-10-12B9