




### Standard Barrel Copper Lug

T&B Catalog Number: 5412008BS  
UPC Number: 78621092075  
Status: |

#### Description:

Copper One-Hole Lug - Straight Standard Belled End Barrel - max 35KV, 600 kcmil Wire, 1/2" Bolt Size, Tin Plated with Inspection Hole, Green 94



**Where To Buy**

Enter Zip Code:

Enter Quantity:

#### General

Material	Copper
Finish	Tin Plated
Wire Size	600 kcmil
Number of Studs	1
Stud Size	1/2
Tongue Angle	Straight
Barrel Length	Standard
Barrel Shape	Belled End
Tongue Width	Standard
Peep Hole	Y
Marking	Standard
Hole Shape	Round
Die Color	Green
Die Code	94

#### Specifications

Voltage Rating	600V to 35KV
----------------	--------------

#### Tooling

Connector & Tooling Chart [Click Here](#)

#### Packaging

Inner Package	6
Outer Package	60
Package Height	3.43
Package Length	21.5
Package Width	8.5
T&B Sold in UOM	Each
T&B Weight Per UOM	37.9 lbs. per 100

#### Application Support

Overview [Click Here](#)

#### Notes

- Dimensions given for reference only. Dimensions may vary up to +/- .030.

#### Certifications

RoHS Compliance Yes [Generate Compliance Certificate](#)

#### Certifications



File Nbr:  
E9809

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Terminals](#) category:*

*Click to view products by [ABB](#) manufacturer:*

Other Similar products are found below :

[HT-13-10](#) [71M-250-32-NB](#) [01-2065-1-0216](#) [00581P0075](#) [M10-10RX](#) [M10BCK](#) [60205-1](#) [604200-1](#) [60598-1-CUT-TAPE](#) [60617-1-C](#) [60873-1](#) [M14-516R/SK](#) [M14-6RSX](#) [M18-10FLX](#) [M18-8FBX](#) [M18-8R/LX](#) [M18BCK](#) [61314-6-C](#) [61-S](#) [61-SN-A](#) [62-NBM-A](#) [63-S](#) [640179-1](#) [640917-2-CUT-TAPE](#) [6501550002](#) [66107-2-C](#) [66107-4-C](#) [696683-1](#) [696834-1](#) [696861-1](#) [696931-1](#) [696999-1](#) [M8-516RK](#) [M86700006](#) [MA250DMFMX-A](#) [701-2007](#) [701-2307](#) [701-7761-03](#) [70F-110-32-PB](#) [718-N-A](#) [71M-187-20-NBL](#) [71M-250-32-NBL](#) [72F-187-20-NBL](#) [72M-250-32-NBL](#) [7310](#) [73F-250-32](#) [73F-250-32-NBL](#) [73F-250-32-NL](#) [F14-10C](#) [F-1M](#)