





(2,54 mm) .100" (ICF)

(1,27 mm) .050" (PLCC)

ICF, PLCC SERIES



ICF-624-S-O



PLCC-068-F-A

SMT DIP & CHIP CARRIER SOCKETS

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?ICF

Insulator Material:
Black LCP



Contact Material:
BeCu

Plating: Au or Sn over 50µ" (1,27 µm) Ni

Current Rating:
1A per contact

Operating Temp Range:
-55°C to +125°C

Contact Resistance:
10 mΩ

Insertion Depth:
(2,54 mm) .100" to (3,81 mm) .150"

Insertion Force/Contact:
5 oz (1,39 N) average

Withdrawal Force/Contact:
4 oz (1,11 N) average

RoHS Compliant:
Yes

Processing:

Lead-Free Solderable:
Yes

SMT Lead Coplanarity:
.006" (0,15 mm) max

ICF

TIGER EYE™ CONTACT

ROW SPACING & NO. OF CONTACTS

Specify from chart below

"-XXX"	Row Space	No. of Contacts
-308	.300 (7,62)	08
-314		14
-316		16
-318		18
-320		20
-324	.600 (15,24)	24
-328		28
-624		24
-628		28
-632		32
-640		40

PLATING OPTION

-S
=30µ" (0,76 µm) Gold on contact, Matte Tin on tail

-T
= Matte Tin

TAIL OPTION

-I
=Tails In

-O
=Tails Out

OTHER OPTION

-TR
=Tape & Reel Packaging

Note:
Some sizes, styles and options are non-standard, non-returnable.

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?PLCC

Insulator Material:
Black Liquid Crystal Polymer



Contact Material:
BeCu

Plating:
Sn or Au over 50µ" (1,27 µm) Ni

Current Rating:
1A per contact

Operating Temp Range:
-55°C to +105°C

Contact Resistance:
10 mΩ

RoHS Compliant:
Yes

Processing:

Lead-Free Solderable:
Yes

Lead Coplanarity:
Less than 52 leads=.006" (0,15 mm) max;

52 leads and more=.008" (0,20 mm) max

Note:
Some sizes, styles and options are non-standard, non-returnable.

PLCC

NO. OF CONTACTS

-020, -032, -044, -068

NO. OF PINS	A	B	C	D
-020	.600 (15,24)	.600 (15,24)	.370 (9,40)	.370 (9,40)
-032	.700 (17,78)	.800 (20,32)	.470 (11,94)	.570 (14,48)
-044	.900 (22,86)	.900 (22,86)	.670 (17,02)	.670 (17,02)
-068	1.200 (30,48)	1.200 (30,48)	.970 (24,64)	.970 (24,64)

PLATING OPTION

-F
=Gold flash on contact, Matte Tin on tail

-T
Matte Tin


ALIGNMENT PIN OPTION

-N
=No Alignment Pins

-A
=Alignment Pins

PACKAGE OPTION

-TR
=Tape & Reel Packaging



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [IC & Component Sockets](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[714-43-102-31-012000](#) [0066-3-17-15-30-14-02-0](#) [0134-0-15-15-32-27-04-0](#) [614-DG5](#) [6527-0-00-15-00-00-03-0](#) [670](#) [672](#) [673](#) [712-93-120-41-001000](#) [714-93-104-31-018000](#) [8059-4G1-LF](#) [807-22-001-10-001101](#) [807-22-001-10-003101](#) [807-22-001-10-004101](#) [807-22-001-10-006101](#) [807-22-001-30-011101](#) [807-22-001-30-012101](#) [807-22-001-30-013101](#) [807-22-001-30-014101](#) [8-1437531-4](#) [8150-6P10](#) [833-93-034-10-001000](#) [835-43-014-10-001000](#) [851-41-006-10-001000](#) [851-43-008-20-001000](#) [851-43-014-20-001000](#) [851-93-006-20-001000](#) [851-93-010-20-001000](#) [853-43-020-10-001000](#) [86.010.0053.0](#) [116-43-306-41-003000](#) [116-43-308-41-007000](#) [116-87-308-41-007101](#) [PX-68LCC](#) [PX-84LCC](#) [121-13-318-41-001000](#) [121-13-320-41-001000](#) [121-13-308-41-001000](#) [123-43-314-41-801000](#) [123-43-420-41-001000](#) [123-43-636-41-001000](#) [123-87-320-41-001101](#) [122-13-316-41-001000](#) [123-13-624-41-001000](#) [123-43-306-41-001000](#) [123-43-322-41-801000](#) [123-43-428-41-001000](#) [123-43-624-41-001000](#) [12-3513-11](#) [123-91-320-41-001000](#)