

## Braided shielded cables sect. 0,75 mm<sup>2</sup>



FirestoP®



**Applications:**  
Braided shielded cables for data transmission and electronics.

**Characteristics:**  
**Conductors:** stranded in O.F.C. red copper  
**Cond. Insulation:** Flame Retardant PVC CEI 20-22/II°  
**Core colours:** Brown, Blue, Black, Yellow/green, Red, White, Yellow, Grey, Bright-orange, Green, Violet, Pink  
**Total Shield:** Braided covering 85% O.F.C. red copper  
**External Sheath:** Flame Retardant PVC CEI 20-22/II°  
**Sheath colour:** Black

**Max rated Voltage AC:** 49 V.  
**Operative Temperature °C.:** -15° / +70°



tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C 1075	1	1 x 0,75 (18 AWG)	24x0,20	2,3		4,0	100	B	2,6
C 2075	2	2 x 0,75 (18 AWG)	24x0,20	2,3		6,4	100	B	5,8
C 3075	3	3 x 0,75 (18 AWG)	24x0,20	2,3		6,8	100	B	7,8
C 4075	4	4 x 0,75 (18 AWG)	24x0,20	2,3		7,4	100	B	11,0
C 5075	5	5 x 0,75 (18 AWG)	24x0,20	2,3		7,8	100	B	9,0
C 6075	6	6 x 0,75 (18 AWG)	24x0,20	2,3		8,6	100	B	12,0
C 8075	8	8 x 0,75 (18 AWG)	24x0,20	2,3		10,6	100	B	14,5
C10075	10	10 x 0,75 (18 AWG)	24x0,20	2,3		11,2	100	B	15,0
C12075	12	12 x 0,75 (18 AWG)	24x0,20	2,3		11,6	100	B	25,0

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
30		260
30	170	300
30	150	270
30	140	260
30	140	260
30	130	250
30	110	220
30	100	210
30	100	200

## Braided shielded cables sect. 1,00 mm<sup>2</sup>



FirestoP®



**Applications:**  
Braided shielded cables for data transmission and electronics.

**Characteristics:**  
**Conductors:** stranded in O.F.C. red copper  
**Cond. Insulation:** Flame Retardant PVC CEI 20-22/II°  
**Core colours:** Brown, Blue, Black, Yellow/green, Red, White, Yellow, Grey  
**Total Shield:** Braided covering 85% O.F.C. red copper  
**External Sheath:** Flame Retardant PVC CEI 20-22/II°  
**Sheath colour:** Black

**Max rated Voltage AC:** 49 V.  
**Operative Temperature °C.:** -15° / +70°



C 1100	1	1 x 1,00 (17 AWG)	32x0,20	2,5		4,4	100	B	3,0
C 2100	2	2 x 1,00 (17 AWG)	32x0,20	2,5		7,2	100	B	8,0
C 3100	3	3 x 1,00 (17 AWG)	32x0,20	2,5		7,8	100	B	9,0
C 4100	4	4 x 1,00 (17 AWG)	32x0,20	2,5		8,6	100	B	10,0
C 6100	6	6 x 1,00 (17 AWG)	32x0,20	2,5		10,8	100	B	16,0
C 8100	8	8 x 1,00 (17 AWG)	32x0,20	2,5		11,2	100	B	19,0

21		280
21	170	300
21	150	270
21	130	240
21	130	230
21	120	220

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Tasker](#) manufacturer:*

Other Similar products are found below :

[89182-010-1000](#) [89705-008-500](#) [6000FE-877-1000](#) [CS2885-000](#) [M27500-20SP2S23](#) [6300FE-877-U1000](#) [6309UE-877-1000](#) [M3905-BK005](#)  
[6502FE 8771000](#) [6541PA-008-U1000](#) [CV6807-000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-](#)  
[0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [720451-000](#) [752687-000](#) [768146-000](#) [773159-000](#)  
[82841-877-5000](#) [83318E-009-500](#) [8348-060-500](#) [83559-002-1000](#) [83653-002-5000](#) [83659-002-1000](#) [83709-002-1000](#) [8404-060-500](#) [8469](#)  
[060100](#) [858171-000](#) [8628-060-500](#) [868361-001](#) [8730-060-1000](#) [8737-060-U1000](#) [8747-060-100](#) [8747-060-1000](#) [8769-060-1000](#) [8775-060-](#)  
[500](#) [877541-000](#) [8780-060-1000](#) [8782-001-U1000](#) [88444-002-1000](#) [9159-060-500](#) [939870-000](#) [9423 060U500](#) [9444 060U1000](#) [9497](#)  
[0001000](#)