

Microphone cables



Applications:
Microphone cables for sound reproduction.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact PE
 Core colours: White, Yellow, Red, Green
 Waste filler between conductors
 Shield: Braided covering 60%
 O.F.C. red copper
 Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C255	2	2 x 0,22 (24 AWG)	7x0,20	1,2	5,0	100	B	3,0
C256	3	3 x 0,22 (24 AWG)	7x0,20	1,2	5,2	100	B	3,5
C257	4	4 x 0,22 (24 AWG)	7x0,20	1,2	5,5	100	B	4,0

nightly blue®



Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
90	66	113
90	59	103
90	59	106
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

Professional Flat Audio Cable



Firestop®



TSK Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool mt.	Type	Kg.
TSK 1042	2x2	2 x 2 x 0,22 (24 AWG)	28x0,10	1,1	4,5 x 9,1	100	B	6,0

Flat divisible pair balanced microphone cable

nightly blue®



Applications:
Special flat pair cable, more flexible and divisible, suitable for the realization of professional audio-balanced assembly.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact XLPE
 Pair colours: White-Red
 White-Blue
 Drain wire: O.F.C. tinned copper
 Shield: Spiral covering 100%
 O.F.C. red copper
 Sheath: Flame Retardant PVC
 CEI 20-22/II°
 Sheath colour: Blue-night

90	75	160
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

Audio Quad cable



Firestop®



TSK Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool mt.	Type	Kg.
TSK 1044	2x2	2 x 2 x 0,22 (24 AWG)	28x0,10	1,1	5,2	100	B	4,0

Audio Quad cable



Applications:
Flexible pair audio QUAD cable for sound reproduction.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact XLPE
 Pair colours: Transparent-Red
 Transparent-Yellow
 Total taping in unwoven polyester
 Drain wire: O.F.C. tinned copper
 Shield: Braided covering 95%
 O.F.C. tinned copper
 Sheath: Flame Retardant PVC
 CEI 20-22/II°
 Sheath colour: Blue-night

90	65	150
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[59384500100E](#) [73-6310-10](#) [73-6311-10](#) [73-6313-3](#) [73-6313-6](#) [PCX-60-50](#) [RCA10RCA](#) [1-3737-600-3216](#) [15AK25X](#) [25FK25](#) [LF3BLX](#) [30-1511-10](#) [30AR30](#) [30AK30](#) [30AN30](#) [RCA05RCA](#) [RCA05RCAB](#) [RCA05TS](#) [RCA10RCAB](#) [420001400-3](#) [426058900-3](#) [TT6RX](#) [TT7BKX](#) [TT93602](#) [426058300-3](#) [LF1BKX](#) [LF3RX](#) [0887418300](#) [73-6312-6](#) [73-6314-3](#) [73-6352-3](#) [VMP3YX](#) [VMP2YX](#) [68767-0003](#) [TT746](#) [TT744](#) [CN13B](#) [LF4GNX](#) [LF2GYX](#) [426494200-3](#) [LF1RX](#) [VMPBNCF](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [TT747N2](#) [TT864](#) [LF2YX](#) [426491500-3](#) [426523700-3](#)