



Applications:

Flexible cable composed of: 5 mini-coaxial cables for video R.G.B.+H.V. transmission on professional video systems and for Monitors and video-projectors.
Cable for fixed and mobile installation, suitable for the realization of video assembly.

Characteristics:

Conductors: **stranded in O.F.C. red copper**
 Insulations: **PEE**
 Shields: **spiral covering 100% O.F.C. tinned copper**
 Sheaths: **PVC**
 Sheath colours: **Red, Green, Blue, Black, White**
 Total Sheath: **Flame Retardant PVC CEI 20-22/II°**
 Sheath colour: **Grey**



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C263	5	5 x 75 Ω (0,08 mm ²)	10x0,10	1,6	2,8	9,8	100 300 500	B B B	12,0

Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
210				67	
Velocity of propagation of coax %	Impedance	Max rated Voltage	Operative Temperature		
%	Ω ± 3%	V	°C		
66	75	49	-15 / +70		
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
19,5	28,5	41,7	60,2	87,3	103,0



Applications:

Professional cable composed of: 5 mini-coaxial cables for video R.G.B.+H.V. transmission on professional video systems and for Monitors and video-projectors.
Cable for fixed and mobile installation, suitable for the realization of video assembly.

Characteristics:

Conductors: **stranded in O.F.C. tinned copper**
 Insulations: **PPE**
 Shields: **Braided covering 90% O.F.C. tinned copper**
 Sheaths: **Flame Retardant PVC CEI 20-22/II°**
 Sheath colours: **Red, Green, Blue, Black, White**
 Total taping: **unweaved Polyester**
 Total Sheath: **Flame Retardant PVC CEI 20-22/II°**
 Sheath colour: **Black**



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C145	5	5 x 75 Ω (0,08 mm ²)	7x0,12	1,4	2,4	9,2	100	B	11,5

Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
210				67	
Velocity of propagation of coax %	Impedance	Max rated Voltage	Operative Temperature		
%	Ω ± 3%	V	°C		
66	75	49	-15 / +70		
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
19,7	28,7	42,0	61,2	88,5	105,0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Cables](#) / [Video Cables](#) / [RCA Cables](#) category:

Click to view products by [Tasker](#) manufacturer:

Other Similar products are found below :

[59384500100E](#) [73-6310-10](#) [73-6311-10](#) [73-6313-3](#) [73-6313-6](#) [PCX-60-50](#) [RCA10RCA](#) [1-3737-600-3216](#) [15AK25X](#) [25FK25](#) [LF3BLX](#) [30-1511-10](#) [30AR30](#) [30AK30](#) [30AN30](#) [RCA05RCA](#) [RCA05RCAB](#) [RCA05TS](#) [RCA10RCAB](#) [420001400-3](#) [426058900-3](#) [TT6RX](#) [TT7BKX](#) [TT93602](#) [426058300-3](#) [LF1BKX](#) [LF3RX](#) [0887418300](#) [73-6312-6](#) [73-6314-3](#) [73-6352-3](#) [VMP3YX](#) [VMP2YX](#) [68767-0003](#) [TT746](#) [TT744](#) [CN13B](#) [LF4GNX](#) [LF2GYX](#) [426494200-3](#) [LF1RX](#) [VMPBNCF](#) [LF10GNX](#) [427492100-3](#) [LF4BLX](#) [TT747N2](#) [TT864](#) [LF2YX](#) [426491500-3](#) [426523700-3](#)