

Mounting Bases, Cable Ties and Accessories

Great for use with screws, nuts and bolts for secure fastening to surfaces.

Ty-Rap® 6.6 Nylon Mounting Head Ties — Natural



| STD. CAT. NO. | BULK CAT. NO. | BODY WIDTH IN./MM | LENGTH IN./MM | MAX. WIRE BUNDLE DIA. IN./MM | MOUNTING HOLE | TENSILE STRENGTH LBS./N | STD. PKG. QTY. | BULK PKG. QTY. |
|---------------|---------------|-------------------|---------------|------------------------------|---------------|-------------------------|----------------|----------------|
| TY533M | TY33M | .09/2.29 | 4.00/101.60 | .63/16.00 | #4 | 18/80.07 | 100 | 1,000 |
| TY534M | TY34M | .14/3.56 | 6.00/152.40 | 1.13/28.70 | #8 | 40/177.90 | 100 | 1,000 |
| TY535M | TY35M | .18/4.57 | 7.80/198.12 | 1.75/44.45 | #10 | 50/222.40 | 100 | 1,000 |
| TY5354M | TY354M | .18/4.57 | 14.60/370.84 | 4.00/101.60 | #10 | 50/222.40 | 100 | 1,000 |
| — | TY635M | .19/4.83 | 7.80/198.12 | 1.77/44.96 | #6 | 50/222.40 | — | 1,000 |
| TYF535M | TYF35M | .19/4.83 | 7.24/183.90 | 1.77/44.96 | #6 | 50/222.40 | 100 | 1,000 |
| TY537M | TY37M | .30/7.62 | 13.90/353.06 | 3.50/88.90 | ¼" | 120/533.80 | 50 | 500 |

For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).

- Natural nylon color

Ty-Rap® 6.6 Nylon Mounting Head Ties — Weather Resistant

The MX series cable ties are recommended for outdoor use. The addition of carbon black provides good ultraviolet resistance and prolongs the useful life of the cable tie.




| STD. CAT. NO. | BULK CAT. NO. | BODY WIDTH IN./MM | LENGTH IN./MM | MAX. WIRE BUNDLE DIA. IN./MM | MOUNTING HOLE | TENSILE STRENGTH LBS./N | STD. PKG. QTY. | BULK PKG. QTY. |
|---------------|---------------|-------------------|---------------|------------------------------|---------------|-------------------------|----------------|----------------|
| TY533MX | TY33MX | .09/2.29 | 4.00/101.60 | .63/16.00 | #4 | 18/80.07 | 100 | 1,000 |
| TY534MX | TY34MX | .14/3.56 | 6.00/152.40 | 1.13/28.70 | #8 | 40/177.90 | 100 | 1,000 |
| TY535MX | TY35MX | .18/4.57 | 7.80/198.12 | 1.75/44.45 | #10 | 50/222.40 | 100 | 1,000 |
| TY5354MX | TY354MX | .18/4.57 | 14.60/370.84 | 4.00/101.60 | #10 | 50/222.40 | 100 | 1,000 |
| TY537MX | TY37MX | .30/7.62 | 13.90/353.06 | 3.50/88.90 | ¼" | 120/533.80 | 50 | 500 |

For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).

- Black color

Ty-Rap® 6.6 Nylon Push-Mount Ties

For use in 3/16" and ¼" pre-drilled holes. Panel thickness .09" max. (TY554M) Range .04-.156" (TY538M)



| STD. CAT. NO. | BULK CAT. NO. | BODY WIDTH IN./MM | LENGTH IN./MM | MAX. WIRE BUNDLE DIA. IN./MM | MOUNTING HOLE | TENSILE STRENGTH LBS./N | STD. PKG. QTY. | BULK PKG. QTY. |
|---------------|---------------|-------------------|---------------|------------------------------|---------------|-------------------------|----------------|----------------|
| TY554M | TY33MX | .14/3.56 | 5.96/151.38 | 1.13/28.70 | 3/16" | 40/177.90 | 100 | 1,000 |
| TY538M | TY38M* | .18/4.57 | 7.80/198.12 | 1.75/44.45 | ¼" | 50/222.40 | 100 | 1,000 |

*Nylon 6.6 UV weather-resistant version available (TY38MX).

For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).

- Natural nylon color

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [abb manufacturer](#):

Other Similar products are found below :

[TV10-516R](#) [017667013](#) [RF727](#) [2CMA100178R1000](#) [5SDD 92Z0401](#) [ESV14-BS](#) [EZS-21-250](#) [F204AC-40/0.03](#) [F204AC-40/0.1](#) [F362-25/0.03](#) [GJL1211001R0011](#) [GJL1211501R8000](#) [GJL1311001R0101](#) [GJL1311201R0001](#) [GJL1313001R0101](#) [GJL1317201R0001](#) [A40-30-10-84](#) [AF09-30-01-11](#) [AF460-30-11-68](#) [1455](#) [EF45-30](#) [ERG297](#) [HSC2-20](#) [1SAM201904R1001](#) [1SAM350000R1003](#) [1SAZ721201R1009](#) [1SAZ721201R1014](#) [1SAZ721201R1025](#) [1SDA057197R1](#) [1SFA611101R1002](#) [1SFA611130R1103](#) [1SFA611143R1101](#) [1SFA611202R1108](#) [1SFA611203R1108](#) [1SFA611215R1001](#) [1SFA611216R1108](#) [1SFA611285R1002](#) [1SFA611521R1001](#) [1SFA611702R6006](#) [1SFA616162R1025](#) [1SFA619100R3015](#) [1SVR730020R0200](#) [IPC4111](#) [OS30FACC12](#) [OS60GJ03](#) [OVR1N160277PS](#) [OXC1L48](#) [254](#) [S2C-H6RU](#) [2CDS212001R0165](#)