



Art No. UA0149

USB3.0 4-Port Hub

The UA0149 is very well shielded owing to its metallic casing and as such is the optimum solution for an industrial use. It can be mounted below the table or at the wall. This creates order at the work place. The power pack contained in the scope of supply provides for extra power with current hungry USB devices. Also, diagnostic LEDs provide port status for each port and power status.

Features:

- Compliant to USB3.0/2.0/1.1 Specification
- Supports USB3.0 High-Speed up to 5Gbps
- 1 x up-stream port and 4 x down-stream
 LED status indicator ports support
- Connects up to 127 USB devices
- Equipped with over-current Detection & Protection
- With external power adapter (5V, 3.5A)
- Metal housing with mounting rack
- Plug & Play
- Supports Windows XP/Vista/7

Technical Specifications:

Dimensions (W×H×D)	117x20×45 mm	
Weight	130g	
Power Adapter	100-240V AC, 50-60Hz, 3500mA	
Input Voltage	Without Power Adapter	5V DC, 500 mA
	With Power Adapter	5V DC, 3500 mA
Cable Length	0.6m	
Operating Temperature	-5°C to 45°C	
Storage Temperature	-10°C to 60°C	

Package Content:

- 1 x USB3.0 Cable
- 1 x Power Adapter
- 1 x User Manual

Packaging Information:

- 1 x 4-Port USB HUB Packing Dimension: 170x117x60 mm
 - Packing Weight: 0.4kg
 - Carton Dimension: 380x300x300 mm
 - Carton Q'ty: 25pcs
 - Carton Weight: 9kg







X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Specialised Cables category:

Click to view products by Logilink manufacturer:

Other Similar products are found below:

GP-IE515546DS-002 96CB-L2020PIB2 1200740161 R88ACAKA0015SRE R88ACAWL005SDE R88ACRGD0R3C 1300660042

1300660201 1971465-2 22733-8 2R7004A20F060 SSL009PC2DC012N FC2A-KC6C CCSFCBF2 R7ACAB005S XS2WM12PUR4SA10M

XS2WM12PVC4SA10M 05AU05 UCABLE 10114734-2010LF XW2Z010H3 XW2Z010H1 5-1589827-8 5-1589827-4 861084-1

XW2Z200JB24 5-1589956-8 CR4000A76M020 1201140211 1300140039 CR4000A76M005 CR4006A76M005 10077488-N0550FDLF

XW2ZRY150C I4JPBJLUXX100 I4JPBJLUXX50 CM06 CM06W POE004 0243 009 05 0243 009 20 0243 009 36 0243 009 26 0243 009

23 0243 009 01 0243 009 30 0243 008 05 0243 008 20 0243 008 36 0243 008 23