



REV.	DESCRIPTION	DATE	NAME
A0	NEW RELEASE	2007.04.25	修正一
A1	REVISE	2008.06.26	修正一
A2	REVISE	2008.11.12	修正一
A3	EN1107280313	2011.07.28	肖勇

UNIT	SCALE	SHEET	TITLE:
mm	1 of 1		

DRAWN BY	APPROVED BY	GENERAL TOLERANCE	ANGLE
2007.04.25	2007.04.25	2007.04.25	
修正一	修正一		

燦達電子工業股份有限公司
JOINT TECH ELECTRONIC IND. CO., LTD.

I. D. C. HOUSING
5.08mm PITCH

REV.	REV.
A3	

SPECIFICATIONS

Current Rating: 10A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 10mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1500V AC/minute
Terminal: Phosphor Bronze/Tin-plated
Material: Nylon 66,UL94V-2
Color: Natural(Translucent)

Ordering code
C5080 HI-04P XXX
① Series No.
② Connector type: HI=I.D.C.Connector
③ No. of circuits
④ Option code:
-16=AWG#16
-18=AWG#18
-20=AWG#20
-22=AWG#22

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [Joint manufacturer](#):

Other Similar products are found below :

[1600206-1](#) [163-0301-EX](#) [163-0302](#) [163-0308-EX](#) [163-0310-EX](#) [163-1061-EX](#) [163-1100-EX](#) [163-4024](#) [163-4117-EX](#) [163-4118-EX](#) [163-5005-E](#) [163-7421](#) [163-MJ22-EX](#) [171-0721-EX](#) [171-0725-EX](#) [171-3118-EX](#) [171-3210-E](#) [171-3221-EX](#) [171-3222-EX](#) [171-A1326-EX](#) [173-23507-ST-EX](#) [173-5521TIP-EX](#) [173-6330TIP-EX](#) [KLDVX-SMT-02-ATR](#) [KLDX-0201-AHT-1](#) [KLDX-0202-AHT](#) [KLDX-SMT-0202-BP](#) [KLDX-SMT-0202-BPTR](#) [163-0179-EX](#) [163-0307-E](#) [163-0309-EX](#) [163-4007-EX](#) [163-4015-EX](#) [163-4025](#) [163-4119-E](#) [163-4303-E](#) [16PJ101-EX](#) [171-0702-EX](#) [171-0722-E](#) [171-0726-EX](#) [171-2122-EX](#) [171-3216-EX](#) [171-3218-EX](#) [171-3219-EX](#) [171-3220-EX](#) [171-7391](#) [173-3413-ST-EX](#) [173-4017-ST-EX](#) [RAPCBRK](#) [K596](#)