

Sales Drawing

## This document was generated on 02/24/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Overview: Description:	35718-0900 Active Standard Quick-Disconr 4.75mm Tab Slip-On Te AWG (1.31-0.52mm <sup>2</sup> ), L	rminal, Female, 0.51mm Tab Thickness, Wire Range 16-20	
Documents: Drawing (PDF) Product Specificati	ion PS-35703-001 (PDF)	Packaging Specification PK-35718-001 (PDF) RoHS Certificate of Compliance (PDF)	- Ser
Agency Certifi	cation		image - Reference only
CSA	oution	LR95446	
UL		E92853	EU RoHS China RoHS
01		202000	ELV and RoHS
General			Compliant
Product Family		Quick Disconnects	REACH SVHC
Series		35718	Contains SVHC: No
Crimp Quality Equi	ipment	Yes	Low-Halogen Status
Insulated	ipon	No	Low-Halogen
Overview		Standard Quick-Disconnect Terminals	
Product Name		Slip-On	Need more information on product
Type		Quick Disconnect	environmental compliance?
UPC		756054254752	
UF C		750054254752	Email productcompliance@molex.com
Physical			For a multiple part number RoHS Certificate
Barrel Type		Open	Compliance, <u>click here</u>
Gender		Female	Please visit the Contact Us section for any
		No	non-product compliance questions.
Glow-Wire Complia	ant		
Insulation	-4	None	
Lock to Mating Par	rt	Yes	
Material - Metal	A - C	Brass	
Material - Plating N		Tin	Search Parts in this Series
Material - Plating T	ermination	Tin	<u>35718</u> Series
Net Weight		0.400/g	
Orientation		Straight	Use With
Packaging Type		Reel	4.75mm Tab
Plating min - Matin		1.016µm	
Plating min - Term		1.016µm	Application Tooling   FAQ
Polarized to Mating	g Part	No	Tooling specifications and manuals are
Tab Thickness		0.51mm	found by selecting the products below.
Tab Width		4.75mm	Crimp Height Specifications are then
Temperature Rang		-40°C to +105°C	contained in the Application Tooling
Termination Interfa		Crimp or Compression	Specification document.
Wire Insulation Dia	ameter	3.50mm max.	Global
Wire Size AWG		16, 18, 20	Description Product #
Wire Size mm <sup>2</sup>		0.50 - 1.30	
			Mini-Mac™ <u>0638064500</u>
Electrical			Applicator Rear Feed
Voltage - Maximun	n	250V	
Material Info			
Reference - Dr	awing Numbers		
Packaging Specific	-	PK-35718-001	
Product Specificati		PS-35703-001	
Sales Drawing		SD-35718-09*0	

PS-35703-001 SD-35718-09\*0 This document was generated on 02/24/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Terminals category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

HT-13-10 71M-250-32-NB 01-2065-1-0216 00581P0075 M10-10RX M10BCK 60205-1 604200-1 60598-1-CUT-TAPE 60617-1-C 60873-1 M14-516R/SK M14-6RSX M18-10FLX M18-8FBX M18-8R/LX M18BCK 61314-6-C 61-S 61-SN-A 62-NBM-A 63-S 640179-1 640917-2-CUT-TAPE 6501550002 66107-2-C 66107-4-C 696683-1 696834-1 696861-1 696931-1 696999-1 M8-516RK M86700006 MA250DMFMX-A 701-2007 701-2307 701-7761-03 70F-110-32-PB 718-N-A 71M-187-20-NBL 71M-250-32-NBL 72F-187-20-NBL 72M-250-32-NBL 7310 73F-250-32 73F-250-32-NBL 73F-250-32-NL F14-10C F-1M