

770-006S2
Type 2 Zero Halogen
90° Lipped Adapter Shrink Boots, Long Tail



Lipped 90°

Type 2 Low Smoke Zero Halogen (LSZH) For Regulated Environmental Safety Applications



Halogen-free semi-flexible polyolefin boots meet low smoke and toxicity requirements of shipboard, transit and aircraft systems. These Low Smoke/Zero Halogen (LSZH) boots fit most standard shrink boot adapters, including M85049 types along with Glenair Series 31 and Series 44 adapters. Oxygen index greater than 30%, smoke index less than 20, and toxicity index under 3 per 100 grams. Material meets requirements of NAVSEA 5617649, VG95343 Part 29, BSG 198-5-DF, EN62329-101 and SAE AS5258 Type G. Good resistance to oils, fuels and solvents. Available with high temperature hot melt adhesive lining, these long tail boots provide environmental protection to connector/cable transitions, and enhanced cable strain relief compared to standard length boots. Temperature rating -30° to +135° C. Black color.

- **Low Smoke, Zero Halogen**
- **Meets U.S. and E.U. toxicity requirements.**
- **-30° C to +135° C**

Add "-DH" to the end of any part number for drain holes.

Add "-PP" to the end of any part number for potting ports.

| Boot Size | Part Number | | | |
|-----------|-----------------------------|--------------------------------------|--------------------------------------|----------------------------------|
| | No Adhesive Lining | Pre-Coated with W1 Hot-Melt Adhesive | Pre-Coated with W2 Hot-Melt Adhesive | Pre-Coated with R Epoxy Adhesive |
| 02 | 770-006A202 | 770-006A202W1 | 770-006A202W2 | 770-006A202R |
| 03 | 770-006A203 | 770-006A203W1 | 770-006A203W2 | 770-006A203R |
| 04 | 770-006A204 | 770-006A204W1 | 770-006A204W2 | 770-006A204R |
| 05 | 770-006A205 | 770-006A205W1 | 770-006A205W2 | 770-006A205R |
| 06 | 770-006A206 | 770-006A206W1 | 770-006A206W2 | 770-006A206R |
| 07 | 770-006A207 | 770-006A207W1 | 770-006A207W2 | 770-006A207R |
| 08 | 770-006A208 | 770-006A208W1 | 770-006A208W2 | 770-006A208R |
| 09 | 770-006A209 | 770-006A209W1 | 770-006A209W2 | 770-006A209R |

C

770-006S3
Type 3 Flexible Polyolefin 90° Lipped Adapter Shrink Boots, Long Tail

Type 3 Flexible Polyolefin For General Duty Applications



Economical flexible polyolefin boots fit standard shrink boot adapters, Glenair Series 31 and Series 44 adapters. These self-extinguishing boots meet the requirements of SAE AS81765/1 Type 1. Good resistance to oils and fuels. Available with optional hot melt adhesive lining, these long tail boots provide environmental protection to connector/cable transitions, and enhanced cable strain relief compared to standard length boots, and are ideally suited for heat-sensitive cables due to the material's low heat shrink temperature of +100° C. Temperature rating -55° to +135° C. Black color.

- **General purpose harnessing**
- **Economical, flexible**
- **-55° C to +135° C**

Add "-DH" to the end of any part number for drain holes.

Add "-PP" to the end of any part number for potting ports.

| Boot Size | Part Number | |
|-----------|-----------------------------|---|
| | No Adhesive Lining | Pre-Coated with W2 Standard Hot-Melt Adhesive |
| 02 | 770-006A302 | 770-006A302W2 |
| 03 | 770-006A303 | 770-006A303W2 |
| 04 | 770-006A304 | 770-006A304W2 |
| 05 | 770-006A305 | 770-006A305W2 |
| 06 | 770-006A306 | 770-006A306W2 |
| 07 | 770-006A307 | 770-006A307W2 |
| 08 | 770-006A308 | 770-006A308W2 |
| 09 | 770-006A309 | 770-006A309W2 |

Dimensions in inches (millimeters) and are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [Glenair](#) manufacturer:

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR8248-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [611112-000](#) [617867N001](#) [6500750004](#) [CZ1420-000](#) [D-306-38](#)
[770-003S106W2](#) [770-005S105W1](#) [770-005S106W1](#) [770-007A303](#) [770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [790-3012](#) [MFT-MT2000-NO.14-0-SP](#) [MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#)
[MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#) [MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-1-6"-Clear](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-316-6"-Clear](#) [FP301-332-6"-Black](#) [912229N002](#)
[120-126-16BL](#) [121-001-09](#) [121-018-32](#)