

**770-007S2**  
**Type 2 Zero Halogen**  
**Straight Lipped Adapter Shrink Boots, High Ratio**



**Type 2 Low Smoke Zero Halogen (LSZH) For Regulated Environmental Safety Applications**



Straight lipped high ratio boots are used when the cable or wire bundle is much smaller diameter than the adapter. Halogen-free semi-flexible polyolefin meets low smoke and toxicity requirements of shipboard, transit and aircraft systems. These Low Smoke/Zero Halogen (LSZH) boots fit most standard shrink boot adapters, including AS5258 types along with Glenair Series 31 and Series 44 adapters. Oxygen index greater than 30%, smoke index less than 20, and toxicity index under 3 per 100 grams. Material meets requirements of NAVSEA 5617649, VG95343 Part 29, BSG 198-5-DF, EN62329-101 and SAE AS5258 Type G. Good resistance to oils, fuels and solvents. Available with high temperature hot melt adhesive lining, these boots provide strain relief and environmental protection to connector/cable transitions. Temperature rating -30° to +125° C. Black color.

- *Low Smoke, Zero Halogen*
- *Meets U.S. and E.U. toxicity requirements.*
- *-30° C to +135° C*

Boot Size	Part Number			
	No Adhesive Lining	Pre-Coated with W1 Hi-Temp Hot-Melt Adhesive	Pre-Coated with W2 Standard Hot-Melt Adhesive	Pre-Coated with R Epoxy Adhesive
03	<a href="#">770-007S203</a>	<a href="#">770-007S203W1</a>	<a href="#">770-007S203W2</a>	<a href="#">770-007S203R</a>
04	<a href="#">770-007S204</a>	<a href="#">770-007S204W1</a>	<a href="#">770-007S204W2</a>	<a href="#">770-007S204R</a>
06	<a href="#">770-007S206</a>	<a href="#">770-007S206W1</a>	<a href="#">770-007S206W2</a>	<a href="#">770-007S206R</a>
07	<a href="#">770-007S207</a>	<a href="#">770-007S207W1</a>	<a href="#">770-007S207W2</a>	<a href="#">770-007S207R</a>

**770-007S3**  
**Type 3 Flexible Polyolefin**  
**Straight Lipped Adapter Shrink Boots, Long Tail**

**Type 3 Flexible Polyolefin For General Duty Applications**



Straight lipped high ratio boots are used when the cable or wire bundle is much smaller diameter than the adapter. Economical flexible polyolefin boots fit standard M85049 shrink boot adapters, Glenair Series 31 and Series 44 adapters. These self-extinguishing boots meet the requirements of SAE AS81765/1 Type 1. Good resistance to oils and fuels. Available with optional hot melt adhesive lining, these boots provide strain relief and environmental protection to connector/cable transitions, and are ideally suited for heat-sensitive cables due to the material's low heat shrink temperature of +100° C. Temperature rating -55° to +135° C. Black color.

- *General purpose harnessing*
- *Economical, flexible*
- *-55° C to +135° C*

Boot Size	Part Number	
	No Adhesive Lining	Pre-Coated with W2 Standard Hot-Melt Adhesive
03	<a href="#">770-007S303</a>	<a href="#">770-007S303W2</a>
04	<a href="#">770-007S304</a>	<a href="#">770-007S304W2</a>
06	<a href="#">770-007S306</a>	<a href="#">770-007S306W2</a>
07	<a href="#">770-007S307</a>	<a href="#">770-007S307W2</a>

Dimensions in inches (millimeters) and are subject to change without notice.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:*

*Click to view products by [Glenair](#) manufacturer:*

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR8248-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [617867N001](#) [6500750004](#) [D-306-38](#) [770-003S106W2](#) [770-005S105W1](#) [770-005S106W1](#) [770-007A303](#) [770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [790-3012](#) [MFT-MT2000-NO.14-0-SP](#) [MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#) [MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-1-6"-Clear](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-316-6"-Clear](#) [FP301-332-6"-Black](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#) [121-018-40](#) [121-123-1-1-32BTC](#)