





1 - UNIT INCLUDES 8HM103 BASIC SWITCH 2 - SWITCH HERMETICALLY SEALED PER

MIL-S-8805, SYMBOL 5
3 - ALL EXPOSED PARTS ARE CORROSION
RESISTANT MATERIALS OR SURFACE

LEADWIRE PER MIL-W-22759/10-20 AND 36 INCHES LONG REF

ELECTRICAL DATA

CONTACT ARRANGEMENT SPNC

28 VOLTS DC RATING

INDUCTIVE___ SEA LEVEL _ 1/4 AMP 70,000 FT _ 1/4 AMP

RESISTIVE___ SEA LEVEL _ 1 AMP $70,000 \text{ FT } _ 1 \text{ AMP}$

CHARACTERISTICS

OPERATING FORCE_____5 LBS MAX

RELEASE FORCE_____12 OZ MIN

PRETRAVEL_____ 006 MIN

DIFFERENTIAL TRAVEL____ 015 MAX

OVERTRAVEL____.025MIN

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH A DIVISION OF HONEYWELL THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

MICRO SWITCH a Honeywell Division

FED MFG CODE 91929

SWITCH-BASIC

CATALOG LISTING 38HM4 SUNSTRAND DRAWING 5903922

SCALE 21 DO NOT SCALE PRINT UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ONE PLACE (0) \pm 030 TWO PLACES (00) \pm 015 THREE PLACES (000) \pm 005 ANGLES WEIGHT

THIRD ANGLE PROJECTION

***** -----

8HM4

3

 \mathbf{Z}

DRAWING NUMBER

9

A PR12536 8 NOV 83 B CO55506

25 JUN 84

B C055465

3 K.E. W.
4 C C055828

4 SEP84

D C056632

KEW.
29JAN85
E C069973

TSM
15 MAR 91

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Basic / Snap Action Switches category:

Click to view products by Honeywell manufacturer:

Other Similar products are found below:

83228001 01.098.1358.1 602EN1-6B 602EN532 602EN535-RB 602HE5-RB1 604HE162 604HE223-6B 624HE17-RB 6HM89 6PA78-JM
6SE1 6SX1-H58 70500840 MBD5B1 MBH2731 73-316-0012 79211759 79211923 79218589 7AS12 ML-1155 ML-1376 831010C3.0
831060C3.TL 831090C2.EL 83131904 84212012 8AS239 8HM73-3 903VB1-PG 914CE1-6G PL-100 11SM1077-H4 11SM1077-H58
11SM1-TN107 11SM405 11SM703-T 11SM8423-H2 11SX37-T 11SX48-H58 11SX55-H58 11SM2442-T 11SM76-T 11SM77-H58
11SM77-T 11SM863-T 11SM866 11SX47-H58 A7CN-1M-1-LEFT