

Heat Shrink Tubing HDT-A Thick Wall Adhesive Coated Tubing

Data Sheet

Product Description

HDT-A is a thick wall polyolefin tubing. The toughness and weatherability of the tubing make it well suited for exposed applications. HDT-A is supplied with a specially designed hot melt adhesive layer. The adhesive is applied during extrusion of the tubing thus achieving a very smooth, constant adhesive layer, which ensures excellent sealing properties. HDT-A meets the longitudinal sealing requirements of VDE 0278 part 3 and is, therefore, ideal for sealing underground or exposed inline joints and terminations.

Technical Features			
Continuous operating	-55°C to +130°C	Shrink ratio:	Up to 4:1
temperature range:	Outer wall only		
Base material:	Polyolefin	Shrink temperature:	135°C (min)
Flammability	Self extinguishing	Longitudinal change:	-10% max
	Outer wall only		
Tensile strength:	20 N/mm ² total wall	Dielectrical stength	110 kV/cm
Specifications:	Germanischer Lloyd Type S	VDE 0278 part 3	MIL-I-23053/15
	Vureau Veritas 2557/4889	Lloyds Register of Shipping	

Note: Det Norske Veritas version available (MDT-A-F471)

Ordering Information Type HDT-A							
Bore as supplied minimum (mm)	Bore recovered maximum (mm)	Wall thickness fully recovered total wall (mm)	Wall thickness fully recovered meltable wall (mm)	Standard pack 1.0M length (M)	Standard Colour		
12.0	3.0	3.2	0.7	100			
19.0	6.0	3.3	0.8	100			
30.0	8.0	4.8	0.8	40			
38.0	12.0	4.8	0.8	30	Black		
48.0	15.0	4.8	0.8	15			
85.0	26.0	4.8	0.8	8			
115.0	38.0	4.8	0.8	5			

Technical information provided by 3M is based on experience and/or tests believed to be reliable, but their accuracy is not guaranteed and the results may not be relevant to every user's application. For this reason 3M does not accept responsibility or liability, direct or consequential, arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence. All questions of liability relating to 3M products are governed by the seller's terms of sale subject where applicable to the prevailing law. If any goods supplied or processed by or on behalf of 3M prove on inspection to be defective in material or workmanship, 3M will (at its option) replace the same or refund to the Buyer the price paid for the goods or services. Except as set our above, all warranties and conditions, whether express or implied, statutory or otherwise are excluded to the fullest extent permissible at law. 3M is a trademark of the 3M Company. Printed in the UK. © 3M United Kingdom PLC, 2003.

3M UK PLC Electrical Products 3M Centre, Cain Road Bracknell, Berkshire RG12 8HT Telephone: 01344 858616

Fax: 01344 858758

3M Ireland Sales Office 3M House, Adelphi Centre Dun Laoghaire, Co Dublin, Ireland Telephone: 353 1 280 3555

Fax: 353 1 280 3509

Sales Office PO Box 393 Bedford MK41 0YE Telephone: 01234 229462 Fax: 01234 229433

3M UK PLC

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Tubing and Sleeves category:

Click to view products by 3M manufacturer:

Other Similar products are found below:

770-006S102 5685710001 CR8248-000 CR9960-000 603312-4 607381P039 611112-000 617867N001 6500750004 CZ1420-000 D-306-38 770-003S106W2 770-005S105W1 770-005S106W1 770-007A303 770-010Y106W1 770-010Y706W1 7771210001 MFP-1/4"-Clear MFP-3/64"-Clear 790-3012 MFT-MT2000-NO.14-0-SP MHHT-4-15K2-G-104 MIL-LT-1/2-4-SP MIL-LT-1/2-9-STK MIL-LT-1/2-2-STK MIL-LT-3/0-SP MIL-LT-3/32-0-SP MIL-LT-3/32-6-SP MIL-LT-3/4-6-SP MIL-LT-3/8-0-SP 8159270001 839602-000 8423-6 FP301-116-6"-Black FP301-1/2-48"-Black FP301-12-48"-Black-Hdr FP301-1/4-48"-Black FP301-1/4-48"-White-Hdr FP301-18-48"-Black-Hdr FP301-1/8-6"-Black FP301-18-6"-Black FP301-316-48"-Blue-Hdr FP301-316-6"-Clear FP301-332-6"-Black 912229N002 120-126-16BL 121-001-09 121-018-32 121-018-32 121-018-40