



Home > Search Tools > Part Number

## Part Number Search

You Searched For:  Go

**Note:** Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS.  
 ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Global Sales Locator" located either to the right of this data or at the top of every page.

- [Sales Support](#)
- [Product Overview](#)
- [Stock Check](#)
- [Product Home](#)

The requested part number is currently unsupported in our on-line configuration system. (d)

<p>Product Datasheet</p> <p>Shell Style</p> <p>Endbell Style</p> <p>Gender</p> <p>Shell Size</p> <p>Contact Arrangement</p> <p>Number of contacts</p> <p>Contact Type</p> <p>Contact Plating</p> <p>Shell Material</p> <p>Shell Plating</p> <p>Insulator and Gromet Material</p> <p>Contact Material</p> <p>Water Tightness</p> <p>Operating Temperature</p> <p>Mating Cycles</p> <p>Vibration</p> <p>Contact Rating AWG20</p> <p>Insulator Resistance</p> <p>Test Voltage</p> <p>Operating Voltage</p> <p>Safety Provisions</p> <p>General Info</p> <p>Harnessing Info: Contact Cross-Section</p> <p>Harnessing Info: Insulator Diameter</p>	<p>Cable connecting plug without Endbell but with grommet and ferrule</p> <p>Pin</p> <p>20</p> <p>20-41</p> <p>41 contacts size 20</p> <p>Crimp Contacts (enclosed - not installed)</p> <p>Copper alloy, gold plated</p> <p>Aluminium alloy</p> <p>Olive drab chromate over cadmium plating</p> <p>Polychloroprene</p> <p>Copper alloy, gold plated</p> <p>Acc. To VG95319 Part 2, Test No. 5.9.2</p> <p>-55°/+125°C</p> <p>(-67/257°F)</p> <p>500 min</p> <p>200 m/s<sup>2</sup> at 10 to 2000 Hz</p> <p>7.5 A</p> <p>≈5000 MOhm</p> <p>1500 Vrms</p> <p>In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41.</p> <p>IP67 acc. to DIN 40 050</p> <p>(0,2 bar pressure over 48 hrs)</p> <p><i>All tests in accordance with VG95319 and/or if applicable with VG95210</i></p> <p><a href="#">See assembly instruction</a></p> <p><a href="#">See assembly instruction</a></p>
---	--

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circular DIN Connectors](#) category:*

*Click to view products by [ITT](#) manufacturer:*

Other Similar products are found below :

[CTV06RQF-25-8SA-LC](#) [CTV06RQF-25-8S-LC](#) [CTV06RQW-25-8SB-LC](#) [CTV06RW-25-20P](#) [CTV06RW-25-20PA](#) [CTV06RW-25-20PB](#)  
[CTV06RW-25-20PE-LC](#) [CTV06RW-25-20SB](#) [CTV06RW-25-20SE](#) [CTV07RW-17-8S\(506\)](#) [CTVP00RW-19-32S\(506\)](#) [CTVP00RW-9-35S\(506\)](#) [M83723/71R20416](#) [M83723/71R22196](#) [M83723/71W2039N](#) [M83723/71W24196](#) [M83723/71W2419N](#) [M83723/72A1404N-LC](#)  
[M83723/72R1203N](#) [M83723/72W20418](#) [M83723/72W22126](#) [M83723/72W22556](#) [M83723/72W2419N](#) [M83723/72W2461N](#)  
[M83723/73R2028N](#) [M83723/73R2039N](#) [M83723/73W1412N](#) [M83723/73W2039N](#) [M83723/74R1624N](#) [M83723/74R1808N](#)  
[M83723/74R2212N](#) [M83723/74W1203N](#) [M83723/74W1412N](#) [M83723/74W20416](#) [M83723/74W2041N](#) [M83723/75R10058](#)  
[M83723/75W2232N](#) [M83723/76R14157](#) [M83723/76R20256](#) [M83723/76W1808N](#) [M83723/76W2016N](#) [M83723/76W2461N](#)  
[M83723/77W2016N](#) [M83723/78R22327](#) [M83723/78W2212N](#) [M83723/78W22556](#) [M85049/50-5F](#) [D38999/20FF11AC](#) [D38999/20FJ20BB](#)  
[D38999/20FJ20SC](#)