



DETAIL "B"
SCALE:6:1

DETAIL "A"
SCALE:6:1

SPECIFICATION MODEL: KS-202
 △ RATING: 15A 250VAC (UL/ CUL)
 △ 10A 250VAC (VDE/CCC/SEMIKO/ DEMKO/FIMKO/NEMKO)
 INSULATION RESISTANCE: 100MΩ, DC 500V
 DIELECTRIC STRENGTH: 2000VAC FOR 1 MINUTE
 MEET UL 498 & IEC/EN60320 REQUIREMENTS

NOTE:
 MATERIAL: NYLON66+GF5% 94V-0

REVISION	DESCRIPTION	REVISED BY	TOLERANCES	ANGLE	UNIT	PART NAME	DWG NO
			X±0.1	XX±0.05	mm	KS-202 規格圖	S0301F
▽		孫斌			1:1		
△	端子改變後修改尺寸, 增加安裝.	梁春林					
△	配合客戶面板將卡耳增加一齒.	唐雙軍					

REVISION	DESCRIPTION	REVISED BY	TOLERANCES	ANGLE	UNIT	PART NAME	DWG NO
			X±0.1	XX±0.05	mm	KS-202 規格圖	S0301F
▽		孫斌			1:1		
△	端子改變後修改尺寸, 增加安裝.	梁春林					
△	配合客戶面板將卡耳增加一齒.	唐雙軍					



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [AC Power Entry Modules](#) category:

Click to view products by [Canal manufacturer](#):

Other Similar products are found below :

[0098.0050](#) [6-1609987-9](#) [6167.0002](#) [7-6609955-2](#) [FN389-4-22](#) [FN9233ER-12-06](#) [FN9233S1-10-06](#) [FN9233S1-8-06](#) [FN9233S1B-8-06](#)
[FN9233S1R-1-06](#) [FN9233S1R-12-06](#) [FN9233SB-1-06](#) [FN9233SB-12-06](#) [FN9233SB-8-06](#) [FN9233SR-10-06](#) [FN9233SR-3-06](#) [FN9244B-15-06](#)
[HI](#) [FN9244EB-3-06](#) [FN9244EB-8-06](#) [FN9244ER-15-06](#) [FN9244ER-8-06](#) [FN9244ES1-8-06](#) [FN9244ESB-8-06](#) [FN9244EU-6-06](#)
[FN9244R-12-06](#) [FN9244R-3-07](#) [FN9244R-8-06](#) [FN9244S1-10-06](#) [FN9244S1-12-06](#) [FN9244S1-3-06](#) [FN9244S1B-6-06](#) [FN9244S1R-3-06](#)
[FN9244S-6-06](#) [FN9244SB-10-06](#) [FN9244SB-6-06](#) [FN9244SB-8-06](#) [FN9244SR-10-06](#) [FN9244SR-6-06](#) [FN9244U-3-06](#) [FN9244U-8-06](#)
[FN9260A-6-06](#) [PE00SSSXB](#) [Fuse-H-EUR-1](#) [Fuse-H-USA-1](#) [PM00XD000](#) [PS0SSDBX0](#) [PS0SXSH3B](#) [A-0701-HT-H](#) [RAPC3FG](#) [15EJMS8](#)