



Heavy Duty Differential Pressure Manometer

Wide range dual input With multiple units and RS-232 interface

Features:

- · Dual differential inputs with internal sensors
- Wide (±802 inches of water) measurement range with high resolution
- · Displays 8 types of pressure units: mbar, psi, kg/cm², mmHg, inHg, mH2O, inH2O, and atm
- Record/Recall MIN and MAX readings
- Data Hold and Auto Power off
- · Zero function for offset measurements
- Basic accuracy: ±1% of full scale (includes hysteresis)
- Large dual LCD display
- Metal input connections with two quick-disconnect fittings
- Built-in RS-232 PC interface with optional Data Acquisition software and datalogger
- · Includes 2 quick disconnect-fittings, 9V battery, protective rubber holster with stand, and carrying case





Specifications	Range	Resolution	Basic Accuracy
mbar	±2000mbar	1mbar	±2%FS
psi	±29psi	0.02psi	±1%FS
kg/cm ²	±2.040kg/cm ²	0.001kg/cm ²	±1%FS
mmHg	±1500mmHg	1mmHg	±1%FS
inHg	± 59.05inHg	0.05inHg	±1%FS
mH₂O	±20.40mH₂0	0.01mH₂0	±1%FS
inH₂0	±802.0inH20	0.5inH ₂ O	±1%FS
atm	±1.974atm	0.001atm	±1%FS
Dimensions	7 x 2.9 x 1.3" (178 x 74 x 33mm)		
Weight	12oz (350g)		

Ordering Information:

407910	Heavy Duty Manometer
407910-NIST	407910 with NIST Certificate
156119	117V AC Adaptor
409997	Soft Vinyl Pouch Carrying Case



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160