

Datasheet for part number DA-15P-1-A-W-N-K87-146

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: ORIGINAL D

Our Catalog Part Number: DA-15P-1-A-W-N-K87-146

Our Global Manufacturing Part Number: 121073-6443

Product Datasheet Standard D-Subminiature General Wire Gauge Range AWG AWG 20-28 Mating Cycles 50 Dielectric Withstanding Voltage 1200 VAC at sea level Current Rating 7.5 A at 85°C / 5 A at 105°C 10 milli Ohm max Contact Resistance -55°/+125° Operating Temperature Salt Spray Test 20 hours Shell Material steel Shell Finish tin Insulator Material Thermoplastic, type PCT UL 94V-0 Insulator Color **Contact Arrangement** 15 contacts size 20 Gender Pin Contact Type turned **Contact Material** copper alloy Contact Finish gold flash (Performance Class 3) **Contact Termination** Right angled solder contact termination at short side of trapezoid **Termination Direction** (Standard) Plastic bracket with grounding brackets with 4-40 Mounting Methode Captive Nut РСВ Pushfit for PCB hold diameter 3.0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

DCM37S732N DAM15P500 DEV09S364GTLF DEM09P032N DDM50P732N DAM15S332N 173109-2218 173109-2466 173109-2436 173109-2435 56F706-005-LI 56F711-015 015-0341-000 015-0372-008 015-8544-011 017041-0005 020419-0104 012-0515-000 012-9507-034 012-9507-114 012-9534-001 020745-0008 609-25P M24308/2-23Z M243082310F M243082410F M243082411F M24308/4-21 CT1A18-11PSA206 CT1N36-5SC CT2-16S-17PS CT2-20-15PCAU CT2-24-12PS CT2-24-28PSF127A206 CT2-32-9PC CT6F9767-14-4-14S-5PC CT6FA10SL-4PS CT7-18-10SC CT7-18-10SCAU CT7-18-12SCAU CT7-18-1PC CT7-18-1PCAU CT7-18-21SCAU M83513/01-FC M83723/76W24619 L/C M85049/48-3-2F 69001-865 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCT99S40X