

Quality Products. Service Excellence.

Audio Open Frame 142 Series

PC Board Mount





Features

- Applications: Driver, Input, Interstage, Isolation
- 100mW power level at 200Hz. 15kHz
- Pin type (0.0375" x .02"), P.C. board mount.
- Economical, open type construction.
- Frequency response 200 Hz. 15 Khz. (+/- 1 db, ref. @ 1 Khz.).
- Total distortion less than 0.5% for outputs at 200 Hz., decreasing at higher frequencies.
- Insertion loss less than 1/2 db.
- Bifilar wound for balanced capacitive and resistance characteristics, on pin bobbins for standard 0.187" grid pin spacing.
- Insulation test 1500V rms.
- Net weight: 0.5 oz.

Notes:

1)The current figure is for maximum unbalanced current.

SCHEMATIC DIAGRAM

2) D.C. resistance shown is for the total primary or secondary windings.

PRIMARY SECONDARY 1 2 3 5

	Nominal Impedance (Ohms)		Max. Primary D.C. current (ma.)	D.C. current (Ohms) +/- 15%	
Part No.	Primary	Secondary	(See Note 1)	Primary	Secondary
142A	10K C.T.	10K C.T.	4	720	925
142B	10K C.T.	2K C.T.	4	720	210
142C	15K C.T.	15K C.T.	4	1020	1390
142D	600 C.T.	600 C.T.	15	44	58

Data subject to change without notice

© 2018. Hammond Manufacturing Ltd. All rights reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Racks & Rack Cabinet Accessories category:

Click to view products by Hammond manufacturer:

Other Similar products are found below:

CR-1727 M00-PLN F2420 F2424 8310-1032-SS 9104 PLFF2000 PLFF6000 GP216 PTFA60000LG H-9163-B AC220-84-1 HEH050BA

1427C3 BAS-5104 N-700-2 190-002 HTL10 HTS10 PC-118 PC-780L PC-79 PC-800 SC4-28 F3024 AKWAMT PLFF1000 GRPB12PG

CG3-340S/12 2CWDP36 2CWDP48 2SSHINGE CP-001BK CPL19431LG1 R570-004-107 M6123-4007-SS TS170 531300535 BRX
12290 C4BD3077SBK1 UPS 7-17-14 PLAIN LP40 5261304-07 CCA26-44-01 706-102 CG3-160G 7112C-PLN ALUM CM10 TS81 7142