

This document is the property of Amphenol Corporation and is loaned to the customer for use in the design and manufacture of products. It is not to be reproduced, copied, or disseminated in any form without the written permission of Amphenol Corporation. Amphenol Corporation reserves the right to modify this document without notice. For more information, see the document or for use any information in this document.



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A		07/11/07	

D-SUB TECHNICAL DATA

SHELL : Steel, 2.5um (100u") min tin over 1.25um (50u") min nickel
 BODY : Glass filled thermoplastic.
 Flame retardant to UL94 V-0
 CONTACTS : brass.
 0.76um(30u") min gold over 0.65um(25u") min nickel
 ELECTRICAL : Voltage rating :1000 V RMS at 50 Hz
 Current rating 5A.
 Insulation resistance >1000 M Ohms
 Contact resistance 20 mOhms max.
 CLIMATIC : Temperature range -55 °C up to 125°C
 MARKING : Amphenol...(Series No.)
 Commercial reference
 Manufacturing date

PRODUCT CODE

L 717 SD D 50 P C309



UNLESS OTHERWISE SPECIFIED		APPROVAL		DATE	
TOLEANCES	METRIC	DRAWN	Iss: peng	07/11/07	
	U.S.	CHECKED	14: wang	07/11/07	
X: +/-	0.50				
XX: +/-	0.30				
XXX: +/-	0.20				
FRACTIONS +/-					
ANGLES +/-	2°				
FOR MATERIALS AND FINISHES					
SEE NOTES					
REMOVE SHARP EDGES					
DIMENSIONS					
U.S.	DIMENSIONS		ANGLE OF PROJECTION		
MM	MM				
TITLE					
Stamped and Formed connector, SD series					
SIZE	DRAWING NO.		SCALE		REV.
A4	C L717SDD50PC309		NONE		A
					SHEET 1 OF 1