

Datasheet for part number DBMZ-9H4SN-K126

Our Catalog Part Number: DBMZ-9H4S-N-K126

Our Global Manufacturing Part Number: 053513-2372

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: COMBO D

Product Datasheet	
General	Combo D Series: D-Subminiature offering mixed layouts
Wire Gauge Range AWG	AWG 8-26
Mating Cycles	50
Contact Arrangement	9H4 (5 contacts size 20, 4 contacts size 8)
Dielectric Withstanding Voltage	500 VAC at sea level
Current Rating Signal Contacts	7.5 max
Current Rating Size 8 Contacts	40 A max
Contact Resistance	10 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	steel
Shell Finish	Tin over nickel plating
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Gender	Socket
Contact Type	Straight PCB US footprint
Contact Material	copper alloy
Contact Finish	30 Micro-inch gold
Mounting Method	.300" (7.6mm) 4-40 Standoff, Boardlock

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

DCM37S732N DAM15P500 DEV09S364GTLF DEM09P032N DDM50P732N DAM15S332N 173109-2218 173109-2466 173109-2436 173109-2435 56F706-005-LI 56F711-015 015-0341-000 015-0372-008 015-8544-011 017041-0005 020419-0104 012-0515-000 012-9507-034 012-9507-114 012-9534-001 020745-0008 609-25P M24308/2-23Z M243082310F M243082410F M243082411F M24308/4-21 CT1A18-11PSA206 CT1N36-5SC CT2-16S-17PS CT2-20-15PCAU CT2-24-12PS CT2-24-28PSF127A206 CT2-32-9PC CT6F9767-14-4-14S-5PC CT6FA10SL-4PS CT7-18-10SC CT7-18-10SCAU CT7-18-12SCAU CT7-18-1PC CT7-18-1PCAU CT7-18-21SCAU M83513/01-FC M83723/76W24619 L/C M85049/48-3-2F 69001-865 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCT99S40X