

Dual Laser InfraRed Thermometer

High IR Temperature Range

Fast 100mS response with highest accuracy at point where dual lasers converge plus Type K input and USB interface

Features:

- High 50:1 distance to target ratio measures smaller surface areas at greater distances
- Dual Laser Targeting indicates ideal measuring distance when two laser points converge to 1" target spot
- Type K thermocouple input from -58 to 2498°F (-50 to 1370°C)
- Lock function for continuous readings
- White backlit multifunction LCD display with bargraph
- Fast 100 millisecond response time
- MAX/MIN/AVG/DIF feature displays highest, lowest, average, and MAX minus Min values
- Adjustable emissivity increases measurement accuracy for different surfaces
- Adjustable High/Low set points with audible alarm alerts user when temperature exceeds the programmed set points
- USB interface includes software
- Tripod mounting feature
- Complete with Type K Temperature probe, USB cable and software, tripod, carrying case and 9V battery



Dual Laser

Our Fastest and Easiest-to-use IR Thermometer

- ✓ Dual lasers identify exact measuring spot when they converge to a single spot
- ✓ Fast response is ideal for quick checks of multiple spots in a process or for catching spikes in temperature




Fast response captures hot spots



Two laser points converge at a distance of 50"/127cm) and form a 1" (2.5cm) spot.



Max hold indicates and holds the peak temperature for easy identification of hot spots



Use the Lock function for continuous data transfer to your PC with the included USB cable & software.

Specifications	42570
Laser Convergence Distance	50" (127cm)
IR Range	-58 to 3992°F (-50 to 2200°C)
Repeatability	±0.5% or 1.8°F/1°C
Basic Accuracy	±(1% of rdg + 2°F/1°C)
Max resolution	0.1°F/°C
Emissivity	0.10 to 1.00 Adjustable
Field of View (Distance to Target)	50:1
Type K Range	-58 to 2498°F (-50 to 1370°C)
Memory	Manually Store/Recall 100 readings
Dimensions	8x6.1x2" (204x155x52mm)
Weight	11.3oz (320g)

Ordering Information:

4257050:1 Dual Laser InfraRed Thermometer

42570-NISTL* 50:1 Dual Laser InfraRed Thermometer w/ NIST

*Limited NIST for Certificate of Traceability from -4 to 1500°F (-20 to 815°C).



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)