VALVE-REGULATED LEAD ACID BATTERIES: INDIVIDUAL DATA SHEET

LC-X1228P/LC-X1228AP



(a) The photo and dimensions represent LC-X1228AP.

Specifications

Nominal Voltage		12V	
Rated Capacity (20 hour rate)		28Ah	
Dimensions	Length	6.496 inches (165 mm)	
	Width	4.921 inches (125 mm)	
	Height	7.07 inches (179.5 mm)	
	Total Height	LC-X1228AP 6.890 inches (175 mm) LC-X1228P 7.067 inches (179.5 mm)	
Approx. mass		24.34 lbs. (11 kg)	
Standard Terminals and Resin	UL94HB M5 Bolt and Nut	LC-X1228P	
	UL94HB M5 Threaded Post	LC-X1228AP	
Optional Terminals and Resin	UL94V-0 M5 Bolt and Nut	♦ LC-P1228P	
	UL94V-0 M5 Threaded Post	♦ LC-P1228AP	

 Please contact Panasonic for availability on optional items. Optional items may be subject to minimum order quantities.


Characteristics

Capacity ^(note) 77°F (25°C)		20 hour rate (1.40A) 10 hour rate (2.65A) 5 hour rate (5.00A) 1 hour rate (21.0A)	28.0Ah 26.5Ah 25.0Ah 21.0Ah	
		1.5 hour rate discharge Cut-off voltage 10.5 V	9.80A	
Internal Resistance		Fully charged battery 77°F (25°C)	Approx. $6.0m\Omega$	
Temperature		104°F (40°C)	102%	
dependency		77°F (25°C)	100%	
of capacity		32°F (0°C)	85%	
(20 hour rate)		5°F (-15°C)	65%	
Self discharge 77°F (25°C)		Residual capacity after standing 3 months	91%	
		Residual capacity after standing 6 months	82%	
		Residual capacity after standing 12 months	64%	
Charge Method (Constant Voltage)	Trickle use	Initial current	4.20 A or smaller	
		Control voltage	13.6V to 13.8V (per 12V cell 25°C)	


(Note) The above characteristics data are average values obtained within three charge/discharge. Cycles not the minimum values.

For standby power supplies. Expected trickle life: Approx. 6 years at 25°C, Approx. 10 years at 20°C.


Dimensions (mm)



Discharge characteristics 77°F (25°C) (Note)



Duration of discharge vs. Discharge current (Note)



Panasonic

VRLA BATTERIES

AUGUST 2005

This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact Panasonic for the latest information.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sealed Lead Acid Battery category:

Click to view products by Panasonic manufacturer:

Other Similar products are found below :

0809-0012 0819-0012 0850-0004 0859-0012 0800-0004 LC-R0612P LC-R061R3P PS-1250F1 APCRBC123 APCRBC124 LCRA1212P NP12-12 NP12-6 NP3.2-12 LC-P0612P LC-R063R4P LC-R067R2P1 LC-R122R2P LC-R0612P1 LC-R127R2P1 LC-X1220AP UP-VW1245P1 2320296 RBC32 RBC11A RBC36-SLT