


Working Without Temperature Control Has its Risks.



The Affordably Priced, Temperature-Controlled WHS 40.


With a temperature range of 200°C to 450°C the new WHS 40 soldering station from Weller eliminates the risk of heat spikes and sinks commonly associated with stations without temperature control. In fact, it stabilizes the temperature so the user doesn't have to worry about overcooking sensitive applications.

And for even more control, the station is nicely equipped with an 18 V low-voltage iron with an ergonomic handle, allowing the user to comfortably get closer to the job at hand.

Heat applications only to the temperature required instead of to a crisp. The new Weller WHS 40 soldering station.

Weller

The Weller WHS 40 Soldering Station.



| Cat. # | Nickel | Long Life | mm | # of tips per card |
|--------|--------|-----------|-----|--------------------|
| S 3 | • | | 3.5 | 3 |
| S 31 | | • | 0.4 | 1 |
| S 32 | | • | 2.0 | 1 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [weller manufacturer](#):

Other Similar products are found below :

[SAS3210TRB](#) [0052918099](#) [0058736839](#) [5BSA](#) [0051612499](#) [005 32 566 99](#) [0054465399](#) [PTH6](#) [HE35](#) [SP40NKUS](#) [T0051387699](#)
[T0051388399](#) [T0051388799](#) [T0051516199](#) [T0053421699](#) [T0053427699](#) [T0053434699](#) [T0053638699](#) [T0058732869](#) [PPT2](#) [PSI5](#) [HEW60P](#)
[LT4X](#) [CT6E7](#) [D650](#) [WPA2](#) [DS209](#) [DS227](#) [RT6](#) [RTW3MS](#) [EPH101](#) [T0051390699](#) [T0051612199](#) [T0051628899](#) [T0052704299](#)
[T0052922299](#) [T0053429699](#) [T0053657199](#) [T0054480299](#) [TC208](#) [WTA3](#) [WSTA6](#) [WDH60](#) [WPT15](#) [WLSK200](#) [WEL.PT-F8](#) [T0058764726](#)
[51617799](#) [700-3057](#) [TNRB 60](#)