

Datasheet for part number DDUY50S

Our Catalog Part Number: DDUY-50S

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*U

Product Datasheet	
General	Low Cost Crimp Connector
Wire Gauge Range AWG	AWG 18-30
Mating Cycles	50, 200, 500
Dielectric Withstanding Voltage	1000 VAC at sea level
Current Rating	5 A max
Contact Resistance	15 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	steel
Shell Finish	yellow chromate over cadmium or zinc
Insulator Material	glass filled Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Contact Arrangement	50 contacts size 20
Gender	Socket
Contact Type	stamped
Contact Material	copper alloy
Contact Finish	gold over nickel
Contact Termination	Crimp
Mounting Methode	Dual Float Mount

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Micro-D Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below :

M243082311F M2430834F M24308/4-6F 65-1920-15 M83513/01-HN M83513/03-A10N M83513/03-B14C M83513/03-D09C M83513/03-D11N M83513/03-G02N M83513/03-G05N M83513/03-G08C M83513/03-G09N M83513/03-G12N M83513/03-H13N M83513/04-E15N M83513/04-G04C M83513/10-E01NP M83513/13-B01NP M83513/13-C01NN M83513/16-A01CP M83513/22-D01NP M83513/25-B01NP 6R2004A30F015 6R4006A28A120 703006A13F060 704002A03F200 705001A13F120 7-1532020-5 748567-1-P MDB1-31SH003 MDM-15PBS-L58 MDM-15PCBRM7T MDM-15PH003B-A174 75-068624-59S MDM-15PH034B MDM-15SH001L MDM-15SH004B MDM-21PH003K MDM-25PH003B-A174 MDM-25PHW01F-A174 MDM-37PH006L-A174 MDM-37PH048M5-A174 MDM-37SCBRP-A174 MDM-51PBS-L56 MDM-51PSF MDM-51SH003M7 MDM-51SSM7-A174 MDM-9PBSP-L58 MDM-9PH003M7