
# 3M<sup>™</sup> Boardmount Socket

2 mm and 2 mm x 2 mm Straight, Solder Tail





- Maximizes use of PC board space
- High temperature dielectric
- "No lead" wave and reflow solder compatible
- Single- and dual row design, 2–40 pins or 4–80 pins
- Mates with pin-strip header products
- RoHS Compliant. See the Regulatory Information Appendix (RIA) in the "RoHS compliance" section of www.3Mconnectors.com for compliance information (RIA E1 & C1 apply)

Date Modified: November 21, 2014

TS-2155-E Sheet 1 of 2

### **Physical**

**Insulation:** 

Material: High Temperature Thermoplastic

Flammability: UL 94V-0

Color: Black

Contact: Copper Alloy

Material: **Plating:** 

Underplating:  $1.25-2.5 \mu m [100 \mu^{"}]$  Nickel

Wiping Area: Flash Gold

Solder Tail Area: 1–3 μm [40–118 μ"] Matte Tin

#### **Electrical**

**Current Rating: 1A** 

**Insulation Resistance:**  $> 5 \times 10_{\circ}$  Ohm at 100 VDC

Withstanding Voltage: 1000 V Transition Resistance: ≤20 mOhm

#### **Environmental**


**Temperature Range:** -40°C to +105°C

**Processing Temperature:** max. 260 °C (Profile per J-STD-020C)

**Moisture Sensitivity Level:** 1 (per J-STD-020C)

UL File No.: E68080

2 mm and 2 mm x 2 mm Straight, Solder Tail



3M is a trademark of 3M Company. **Important Notice** All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M. Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

**Electronic Materials Solutions Division** 6801 River Place Blvd.

Austin, TX 78726-9000 U.S.A. 1-800-225-5373 www.3Mconnectors.com

Please recycle. Printed in USA. © 3M 2014. All rights reserved. RIA-2217B-E

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by 3M manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 891-007-9SS-BST1T 000-34000 0008550134 0009482033 0009507031 57102-F02-18ULF 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 CSU011177004 636-1427 638009-1 641938-9 641991-4 644168-1 644827-2 647662-1 65039-019ELF 65692-001LF 65781-018 65781-047