

This document was generated on 03/04/2016

### PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0436500912

Status: Active

Overview: Micro-Fit 3.0™ Connectors

**Description:** Micro-Fit 3.0™ Right Angle Header, 3.00mm Pitch, Single Row, 9 Circuits, with Solder

Tab, Tin, Glow Wire Compliant, Black

**Documents:** 

3D Model RoHS Certificate of Compliance (PDF)

Drawing (PDF) Product Literature (PDF)

Product Specification PS-43650 (PDF)

#### **Agency Certification**

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series <u>43650</u>

Application Power, Wire-to-Board Comments "High Temperature|So

"High Temperature|Square Pin|Solder Type<P><P>This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <P><P> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <P> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for

possible product options."

Overview Micro-Fit 3.0™ Connectors

Product Literature Order No 987650-5984
Product Name Micro-Fit  $3.0^{\text{TM}}$ UPC 800754770453

**Physical** 

Breakaway No Circuits (Loaded) 9 Circuits (maximum) 9 Color - Resin **Black** Durability (mating cycles max) 30 Flammability 94V-0 Glow-Wire Compliant Yes Mated Height 6.98mm Material - Metal Brass

Material - Metal Bras Material - Plating Mating Tin Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 1.516/g



Series image - Reference only

#### **EU ELV**

**Not Relevant** 

EU RoHS China RoHS

Compliant

**REACH SVHC** 

Not Contained Per

-ED/79/2015 (17 December 2015)

**Halogen-Free** 

**Status** 

Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS ELV Green Image Not Relevant

Search Parts in this Series

43650 Series

**Mates With** 

43645 Micro-Fit 3.0™ Receptacle Housing

Number of Rows

Orientation Right Angle

PCB Locator Yes
PCB Retention Yes
PCB Thickness - Recommended 1.60mm

Packaging Type Embossed Tape on Reel

Pitch - Mating Interface 3.00mm
Plating min - Mating 2.540µm
Plating min - Termination 2.540µm
Polarized to PCB Yes
Shrouded Fully
Stackable No

Temperature Range - Operating -40°C to +105°C Termination Interface: Style Surface Mount

**Electrical** 

Current - Maximum per Contact 5.0A Voltage - Maximum 600V

**Solder Process Data** 

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

003

Process Temperature max. C

260

**Material Info** 

**Reference - Drawing Numbers** 

Product Specification PS-43650
Sales Drawing SD-43650-005

This document was generated on 03/04/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

## Click to view similar products for molex manufacturer:

Other Similar products are found below:

60506-C-50 73108 72903 1062837003 0533241060 68301-1017 71506-C 880504 387790039 53254-0710 85071-0017 387204903

783472003 514412093 0026482195 0191310031 503308-4410 02-09-6102 0008650814 791099208 0039000218 89762-1403 89762-1542

89762-1582 0011404526 00136 0022173102 0026615060 CR4006A30M003 0039532085 58098-0628 0003092041 0008520123

0011030025 0011184017 0022162060 0022552102 01312 M15730061 61432 6150300002 CS63W64 CS8264N CS8365N CS8369

62201-8780 62500-1774 M37730026 63103-50 63443-2215